

ISO 5006:2006-11 (E)

Earth-moving machinery - Operator's field of view - Test method and performance criteria

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Basic dimensions	4
4.1 Light spacing dimensions	4
4.2 Masking dimensions	5
5 Test apparatus	5
6 Machine test configuration	5
7 Performance criteria for additional devices	6
7.1 Performance criteria for mirrors	6
7.2 Performance criteria for CCTV system	6
8 Measurement procedure	6
8.1 Test-surface marking and machine location on the test surface	6
8.2 Positioning of the test apparatus	7
8.3 Measurement of the maskings	8
9 Calculation method	9
9.1 Calculation procedure for the determination of maskings at the visibility test circle or the rectangular 1 m boundary	9
9.2 Computer-simulation	10
10 Evaluation method and performance criteria	11
10.1 Visibility performance criteria on the visibility test circle	11
10.2 Visibility performance criteria for the rectangular 1 m boundary	11
10.3 Visibility maskings that exceed the visibility performance criteria with direct view	15
10.4 Requirements for larger, derivative and other types of earth-moving machines not covered in Table 1	16
11 Test report	17
11.1 Machine details	17
11.2 Drawing	17
12 Visibility information for the operator's instructions	17
Annex A (informative) Dimensions and position of HH and RR	18