

DIN EN 15095:2008-02 (E)

Power-operated mobile racking and shelving, carousels and storage lifts - Safety requirements

| Contents | | Page |
|---|---|-------------|
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Significant hazards | 9 |
| 4.1 | Mechanical hazards | 9 |
| 4.2 | Electrical power hazards | 9 |
| 4.3 | Hazards through ignoring ergonomic principles in machine design | 10 |
| 4.4 | Hazards caused through failure of power supply, failure of machine parts or other functional faults | 10 |
| 4.5 | Hazards arising from inappropriate design or failure of safety systems | 10 |
| 4.6 | Hazards caused through electromagnetic influences | 10 |
| 4.7 | List of significant hazards | 10 |
| 5 | Safety requirements and protective measures | 13 |
| 5.1 | General requirements | 13 |
| 5.2 | Mechanical hazards | 13 |
| 5.3 | Electrical hazards | 20 |
| 5.4 | Ergonomics | 21 |
| 5.5 | Power supply faults, machine parts failing or other malfunctions | 22 |
| 6 | Verification of the safety requirements and/or protective measures | 23 |
| 6.1 | Conformity of safety measures to safety requirements | 23 |
| 6.2 | Design/Manufacturing phase | 25 |
| 6.3 | At the installation site, before power is switched on | 25 |
| 6.4 | Commissioning | 26 |
| 7 | Information for the user | 26 |
| 7.1 | Instruction handbook | 26 |
| 7.2 | Marking | 28 |
| Annex A (informative) Types of power-operated storage equipment | | 30 |
| Annex B (informative) Power-operated mobile storage systems | | 33 |
| Annex C (informative) Rail tolerances for mobile racking | | 35 |
| Annex D (normative) Rack and pinion | | 38 |
| D.1 | Pinion | 38 |
| D.2 | Rack(s) | 38 |
| D.3 | Rack/pinion(s) engagement | 38 |
| Annex E (informative) Chains in vertical carousels | | 40 |

| | |
|---|-----------|
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 98/37/EC | 41 |
| Bibliography | 42 |
| Figures Figure A.1 -- Storage equipment with vertically circulating carriers (vertical carousels) | 30 |
| Figure A.2 -- Storage equipment with horizontally circulating carriers (horizontal carousels) | 30 |
| Figure A.3 -- Storage lift | 31 |
| Figure A.4 -- Mobile shelving | 31 |
| Figure A.5 -- Mobile racking | 32 |
| Figure B.1 -- Clearances to building parts (see 5.2.4.2) | 33 |
| Figure B.2 -- Protective devices and edge clearance according to 5.2.4.3 | 33 |
| Figure B.3 -- Example of a cable barrier | 34 |
| Figure B.4 -- Example of local protection on mobile racking according to 5.2.4.7 | 34 |
| Figure C.1 --Twist of the rail | 35 |
| Figure C.2 -- Maximum absolute vertical tolerances | 35 |
| Figure C.3 -- Maximum relative vertical tolerance | 36 |
| Figure C.4 -- Maximum inclination of the rails | 36 |
| Figure C.5 -- Straightness of the rails | 36 |
| Figure C.6 -- Uneven floor | 37 |
| Figure D.1 -- Rack / pinion(s) engagement | 39 |
| Figure E.1 -- Third deep system | 40 |
| Figure E.2 -- Horizontal system | 40 |
| Tables Table 1 -- List of significant hazards | 11 |
| Table 2 | 24 |