

DIN 28086:2022-11 (E)

Eyelets on apparatuses - Dimensions and maximum loadings

Contents

Page

| | |
|--|----|
| Foreword | 3 |
| 1 Scope | 4 |
| 2 Normative references | 4 |
| 3 Terms and definitions..... | 4 |
| 4 Symbols and abbreviations..... | 5 |
| 5 General | 6 |
| 6 Dimensions, designation..... | 6 |
| 6.1 General | 6 |
| 6.2 Designation example..... | 7 |
| 7 Lifting lug arrangement | 7 |
| 8 Maximum lifting capacities | 9 |
| 8.1 General | 9 |
| 8.2 Maximum shackle forces | 10 |
| 8.3 Maximum lifting lug forces..... | 10 |
| 8.4 Reinforcement plate and throat thicknesses | 11 |
| 8.5 Maximum vessel end load | 11 |
| 9 Material | 12 |
| 10 Welding..... | 12 |
| Annex A (informative) Sample calculation..... | 13 |
| Bibliography | 16 |

Figures

| | |
|---|----|
| Figure 1 — Lifting lug | 6 |
| Figure 2 — Maximum force $F_G = F_L$ for a lifting lug | 7 |
| Figure 3 — Maximum force $F_G = 2 \cdot F_L$ for two lifting lugs and lifting beam..... | 8 |
| Figure 4 — Maximum force F_G for two lifting lugs and a double sling ($F_L = F_G / (2 \cdot \cos \alpha)$) | 8 |
| Figure 5 — Maximum force F_G for three lifting lugs and a triple sling ($F_L = F_G / (3 \cdot \cos \alpha)$)..... | 8 |
| Figure 6 — Force coefficient f | 12 |
| Figure A.1 — Lifting the vessel | 13 |

Tables

| | |
|--|----|
| Table 1 — Symbols and units..... | 5 |
| Table 2 — Lifting lug dimensions | 7 |
| Table 3 — Maximum shackle force F_s in accordance with DIN 82016 or DIN 82101 ^b | 9 |
| Table 4 — Maximum forces F_G for various lifting lug arrangements..... | 10 |
| Table 5 — Force increase factor W | 11 |
| Table 6 — Geometric intermediate value A | 12 |