

DIN EN 14879-4:2008-01 (E)

Organic coating systems and linings for protection of industria I apparatus and plants against corrosion caused by aggressive media - Part 4: Linings on metallic components

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 7 |
| 4 | General | 7 |
| 4.1 | Materials | 7 |
| 4.1.1 | Metallic substrates and semi-finished products | 7 |
| 4.1.2 | Linings | 7 |
| 4.2 | Selection criteria | 9 |
| 4.2.1 | General | 9 |
| 4.2.2 | Aggressive substances | 10 |
| 4.2.3 | Type and frequency of fluid loading | 12 |
| 4.2.4 | Thermal loading | 12 |
| 4.2.5 | Changes in temperature | 12 |
| 4.2.6 | Mechanical loading | 13 |
| 4.2.7 | Climatic influences | 13 |
| 4.2.8 | Additional requirements | 13 |
| 4.3 | Load profile | 13 |
| 4.4 | Design of component | 13 |
| 4.5 | Manufacture of the lining | 13 |
| 4.5.1 | Environmental conditions | 13 |
| 4.5.2 | Surface condition and preparation of the substrate | 14 |
| 4.5.3 | Preparation and application of pre-cut parts of the semi-finished products | 14 |
| 4.5.4 | Lining joints | 15 |
| 4.5.5 | Thermal post treatment | 17 |
| 4.6 | Lined component | 17 |
| 5 | Repair of defects | 17 |
| 6 | Designations | 17 |
| 7 | Packaging, transport, storage and installation | 18 |
| 7.1 | General | 18 |
| 7.2 | Packaging and transport | 18 |
| 7.3 | Storage | 18 |
| 7.4 | Installation | 19 |
| 8 | External finish of surfaces not to be lined | 19 |
| 9 | Testing | 19 |
| 9.1 | General | 19 |
| 9.2 | Basic requirements | 19 |
| 9.2.1 | Resistance to the service fluid | 19 |
| 9.2.2 | Cleaning and neutralizing processes | 19 |
| 9.2.3 | Adhesive strength | 19 |

| | | |
|---|---|----|
| 9.2.4 | Capability of dissipating electrostatic charges | 19 |
| 9.2.5 | Additional requirements | 20 |
| 9.3 | Testing of suitability | 20 |
| 9.3.1 | General | 20 |
| 9.3.2 | Testing of resistance and tightness to the service fluid | 21 |
| 9.3.3 | Testing of adhesive strength | 21 |
| 9.3.4 | Testing of capability to dissipate electrostatic charges | 22 |
| 9.4 | Acceptance inspection | 22 |
| 9.4.1 | General | 22 |
| 9.4.2 | Visual inspection | 22 |
| 9.4.3 | Measurement of lining thickness | 23 |
| 9.4.4 | Testing of Hardness | 24 |
| 9.4.5 | Testing of Adhesion | 25 |
| 9.4.6 | High-voltage testing for tightness | 26 |
| 9.4.7 | Testing of capability to dissipate electrostatic charges (special test) | 27 |
| 9.4.8 | Destructive testing of weld seams (special test) | 27 |
| 9.4.9 | Test report | 27 |
| Annex A (informative) | | 28 |
| Annex B (normative) Material combinations to which the media lists for rubber linings are applicable | | 29 |
| B.1 | Hard rubber linings (media list I) | 29 |
| B.2 | Soft rubber linings | 29 |
| B.2.1 | Butyl rubber, halogenated butyl rubber (media list II) | 29 |
| B.2.2 | Chloroprene rubber (media list III) | 29 |
| B.3 | Test media for the media lists | 29 |
| B.3.1 | General | 29 |
| B.3.2 | Media lists | 30 |
| Annex C (normative) Test fluid groups for verification of suitability for material/media combinations | | 32 |
| Annex D (normative) Testing the dissipating capability | | 35 |
| D.1 | Principle | 35 |
| D.1.1 | Dissipation resistance | 35 |
| D.1.2 | Dissipation resistance to earth | 35 |
| D.2 | Testing of dissipation resistance of test samples | 35 |
| D.2.1 | Test equipment | 35 |
| D.2.2 | Test procedure | 35 |
| D.2.3 | Test report | 36 |
| D.3 | Measurement of dissipation resistance to earth on the completely applied lining | 36 |
| D.3.1 | Test equipment | 36 |
| D.3.2 | Preparation of the lining | 36 |
| D.3.3 | Procedure | 36 |
| D.3.4 | Test report | 37 |
| Annex E (informative) Sample form for acceptance inspection report | | 38 |
| Annex F (informative) A-deviations | | 39 |
| Bibliography | | 40 |