

# ISO 81714-1:2010-06 (E)

## Design of graphical symbols for use in the technical documentation of products - Part 1: Basic rules

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Markers .....</b>	<b>2</b>
<b>5</b>	<b>Design of graphical symbols .....</b>	<b>3</b>
<b>5.1</b>	<b>Graphic representation .....</b>	<b>3</b>
<b>5.2</b>	<b>Design procedure .....</b>	<b>3</b>
<b>6</b>	<b>Design principles .....</b>	<b>3</b>
<b>6.1</b>	<b>Shape .....</b>	<b>3</b>
<b>6.2</b>	<b>Operational state .....</b>	<b>4</b>
<b>6.3</b>	<b>Classes of graphical symbols .....</b>	<b>4</b>
<b>6.4</b>	<b>Combination of graphical symbols .....</b>	<b>4</b>
<b>6.5</b>	<b>Grid; module .....</b>	<b>7</b>
<b>6.6</b>	<b>Line width and module size .....</b>	<b>7</b>
<b>6.7</b>	<b>Lines and arcs .....</b>	<b>7</b>
<b>6.8</b>	<b>Minimum space between parallel lines .....</b>	<b>8</b>
<b>6.9</b>	<b>Hatched and filled areas .....</b>	<b>8</b>
<b>6.10</b>	<b>Connect node .....</b>	<b>8</b>
<b>6.11</b>	<b>Position of a connect node .....</b>	<b>8</b>
<b>6.12</b>	<b>Terminal line .....</b>	<b>8</b>
<b>6.13</b>	<b>Reference point .....</b>	<b>9</b>
<b>6.14</b>	<b>Text assigned to graphical symbols .....</b>	<b>9</b>
<b>6.15</b>	<b>Size of graphical symbols .....</b>	<b>10</b>
<b>6.16</b>	<b>Symbol identifier .....</b>	<b>10</b>
<b>7</b>	<b>Modification of proportions .....</b>	<b>10</b>
<b>8</b>	<b>Variants of graphical symbols .....</b>	<b>10</b>
<b>Bibliography .....</b>		<b>14</b>