

DIN EN 1591-1:2014-04 (E)

Flanges and their joints - Design rules for gasketed circular flange connections - Part 1: Calculation

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | 5 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Notation | 7 |
| 3.1 | Use of figures | 7 |
| 3.2 | Subscripts and special marks | 7 |
| 3.2.1 | Subscripts | 7 |
| 3.2.2 | Special marks | 9 |
| 3.3 | Symbols | 9 |
| 3.4 | Terminology | 14 |
| 3.4.1 | Flanges | 14 |
| 3.4.2 | Loading | 14 |
| 3.4.3 | Load conditions | 14 |
| 3.4.4 | Compliances | 14 |
| 4 | Requirements for use of the calculation method | 22 |
| 4.1 | General | 22 |
| 4.2 | Geometry | 22 |
| 4.3 | Material | 23 |
| 4.4 | Loads | 23 |
| 5 | Checking the assembly for a specified initial tightening bolt force (or torque) | 23 |
| 6 | Calculation parameters | 24 |
| 6.1 | General | 24 |
| 6.2 | Flange parameters | 24 |
| 6.2.1 | General | 24 |
| 6.2.2 | Flange ring | 25 |
| 6.2.3 | Connected shell | 26 |
| 6.2.4 | Flexibility-related flange parameters | 27 |
| 6.3 | Bolt and washer parameters | 28 |
| 6.3.1 | General | 28 |
| 6.3.2 | Effective cross-section area of bolts | 28 |
| 6.3.3 | Flexibility modulus of bolts | 28 |
| 6.3.4 | Geometric parameters for washers and contact surfaces | 28 |
| 6.3.5 | Flexibility modulus of washers | 29 |
| 6.4 | Gasket parameters | 29 |
| 6.4.1 | General | 29 |
| 6.4.2 | Theoretical dimensions | 29 |
| 6.4.3 | Effective dimensions | 29 |
| 6.4.4 | Axial flexibility modulus of gasket | 30 |
| 6.4.5 | Lever arms | 32 |
| 7 | Forces | 33 |
| 7.1 | General | 33 |
| 7.2 | Applied loads | 33 |
| 7.2.1 | Assembly condition ($l = 0$) | 33 |
| 7.2.2 | Subsequent conditions ($l = 1, 2$ | 33 |

| | | |
|--|--|----|
| 7.3 | Compliance of the joint | 34 |
| 7.4 | Minimum forces necessary for the gasket | 35 |
| 7.4.1 | Assembly condition ($l = 0$) | 35 |
| 7.4.2 | Subsequent conditions ($l = 1, 2, \dots$) | 35 |
| 7.5 | Internal forces in assembly condition ($l = 0$) | 35 |
| 7.5.1 | Required forces | 35 |
| 7.5.2 | Accounting for bolt-load scatter at assembly | 36 |
| 7.6 | Internal forces in subsequent conditions ($l = 1, 2, \dots$) | 37 |
| 8 | Load limits | 38 |
| 8.1 | General | 38 |
| 8.2 | Bolts | 38 |
| 8.3 | Gasket | 39 |
| 8.4 | Integral flange and collar | 39 |
| 8.5 | Blank flange | 41 |
| 8.6 | Loose flange with collar | 42 |
| Annex A (informative) Dimensions of standard metric bolts | | 43 |
| Annex B (informative) Tightening | | 44 |
| B.1 | Scatter of initial bolt load of a single bolt -- Indicative values 1- and 1+ for a single bolt ... | 44 |
| B.2 | Scatter for the global load of all the bolts | 44 |
| B.3 | Manual uncontrolled tightening | 45 |
| B.4 | Assembly using torque wrench | 45 |
| B.5 | Assembly using bolt tensioner | 46 |
| Annex C (informative) Flange rotations | | 48 |
| C.1 | General | 48 |
| C.2 | Use of flange rotation | 48 |
| C.3 | Calculation of flange rotations | 48 |
| Annex D (informative) Use of the calculation method | | 50 |
| D.1 | Calculation method principle | 50 |
| D.2 | Mechanical model | 51 |
| D.3 | Required checks | 52 |
| D.4 | Calculation sequence | 52 |
| Annex E (informative) Gasket/flange face friction coefficients examples | | 54 |
| Annex F (normative) Determination of eG_c, l based on a given PQR | | 55 |
| F.1 | Determination of the deflection occurring during a PQR test | 55 |
| F.2 | Determination of the deflection to be taken into account in the calculation | 56 |
| Annex G (informative) Sealing gasket parameter when no leakage rate is specified | | 57 |
| Annex H (informative) Alternative calculation procedure taking into account the plastic deformation of the gasket in subsequent load conditions procedures (after assembly) | | 58 |
| H.1 | Introduction | 58 |
| H.2 | Calculation procedure | 58 |
| H.2.1 | General description | 58 |
| H.2.2 | No additional plastic deformation | 59 |
| H.2.3 | Additional plastic deformation | 59 |
| H.3 | Flat gaskets | 59 |
| H.3.1 | Flat gaskets with small or median deformations | 59 |
| H.3.2 | Flat gaskets with greater deformations | 61 |
| H.4 | Metal gaskets with curved surfaces (Figures 3b, c, e, f) | 62 |
| H.5 | Metal gaskets with octagonal section (Figure 3d) | 62 |

| | |
|--|-----------|
| Annex I (informative) Available, incomplete models for conversion of the leakage rates in different conditions (based on certain flow models) | 63 |
| I.1 Introduction and warning | 63 |
| I.2 Flow theory fundamentals | 63 |
| I.2.1 Transport modes | 63 |
| I.2.2 Case of gases | 64 |
| I.2.3 Case of liquids: Parallel capillary model | 65 |
| I.3 Factors of influence on the leakage rate of gaskets and gasketed joints | 65 |
| I.3.1 List of identified factors | 65 |
| I.3.2 Limits and restriction of the proposed models | 65 |
| I.3.3 Dependence on pressure | 66 |
| I.3.4 Dependence on temperature | 67 |
| I.3.5 Dependence on the type of fluid | 68 |
| I.3.6 Influence of the gasket thickness | 68 |
| I.3.7 Influence of gasket width | 69 |
| I.3.8 Influence of gasket stress | 69 |
| I.3.9 Influence of other factors | 69 |
| I.3.10 Conclusion on the factors of influence | 70 |
| I.4.1 General | 70 |
| I.4.2 Determination of a trend for the leakage rate for the flange connection in "actual" from "reference" conditions | 71 |
| I.4.3 Determination of a trend for the leakage rate for the flange connection in "reference" from "actual" conditions | 72 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC | 74 |
| Bibliography | 75 |