DIN EN 16617:2015-07 (E)

Pipework - Corrugated metal hose assemblies for combustible gas - Performance requirements, testing and marking

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 6

4 Design requirements 7
4.1 General 7
4.2 Nominal size (DN) 8
4.2.1 General 8
4.2.2 Overall length (lO) 8
4.3 Materials 8
4.3.1 General 8
4.3.2 Metal hose, braid, end fittings and ferrules 8
4.3.3 Braid 10
4.3.4 Gaskets 10
4.4 Attachment of end fittings to the corrugated metal hose assembly for gas with or without braid 10
4.5 External protection 10
4.6 End fittings 11
4.7 Electrical conductivity 11
4.8 Hose joining 11
4.9 Flow velocity 11
4.10 Cleanliness 11

5 Performance requirements and tests 11
5.1 General 11
5.2 Pressure resistance 12
5.2.1 Requirements 12
5.2.2 Test 12
5.3 Leak-tightness 12
5.3.1 Requirement 12
5.3.2 Test 12
5.4 High temperature resistance 12
5.4.1 General 12
5.4.2 Requirements 12
5.4.3 High temperature test 12
5.5 Elongation 13
5.5.1 Requirement 13
5.5.2 Test 13
5.6 Impact test 13
5.6.1 Requirement 13
5.6.2 Test 13
5.7 Burst pressure test 15
5.7.1 Requirement 15
5.7.2 Test 15
5.8 Pliability and fatigue 15
5.9 Electrical conductivity 15

6 Self-assessment report 15

7 Installation instruction 15

8 Designation 16

9 Marking 16
9.1 Permanent marking 16
9.2 Marking on label 17

10 Packaging 17

Annex A (normative) Correspondence between the performance tests described by EN ISO 10380 and those of this European Standard 18

Bibliography 19