DIN CEN/TR 13121-5:2020-11 (E)

GRP tanks and vessels for use above ground - Part 5: Example calculation of a GRP-vessel

Contents

Page

European foreword 5

Introduction 6

1 Scope 7

2 General 7

3 Dimensions of the tank 7

4 Building materials 9

5 Loadings (9) 9

6 Limit strain for laminate (8.2.2) 11

7 Influence factors (7.9.5.2) 11

8 Partial safety factors (Table 12) 12

9 Combination factors (Table 11) 12

10 Analysis of the cylinder 12
10.1 Influence factor A5 12
10.2 Characteristic strength values 13
10.3 Moduli of elasticity 13
10.4 Analysis of the cylinder in axial direction 13
10.4.1 Proof of strength (Ultimate limit state) 14
10.4.2 Proof of strain (Serviceability limit state) 17
10.4.3 Stability proof (Ultimate limit state) 19
10.5 Analysis of the cylinder in tangential direction 21
10.5.1 Strength analysis (Ultimate limit state) 21
10.5.2 Proof of strain (Serviceability limit state) 23
10.5.3 Stability proof for the cylindrical shell tangential (Ultimate limit state) 23
10.5.4 Critical buckling pressure for rings (Ultimate limit state) 24
10.6 Earthquake design of the cylinder 26
10.6.1 Analysis of the cylinder in axial direction 26
10.6.2 Analysis of the cylinder in tangential direction 29

11 Opening in the cylinder 30
11.1 Analysis in circumferential direction 31
11.1.1 Proof of strength 31
11.1.2 Proof of strain 31
11.2 Analysis in axial direction 32
11.2.1 Proof of strength 32
11.2.2 Proof of strain 32

12 Analysis of the skirt 33
12.1 Internal forces of the skirt 33
12.2 Proof of strength (Ultimate limit state) 34
12.2.1 Design value of actions 34

12.2.2 Design value of corresponding resistance 34
12.2.3 Verification 35
12.3 Proof of strain (Serviceability limit state) 35
12.3.1 Design value of actions 35
12.3.2 Limit design value of serviceability criterion 35
12.3.3 Verification 35
12.4 Stability proof (Ultimate limit state) 35
12.4.1 Design value of actions 35
12.4.2 Design value of corresponding resistance 36
12.4.3 Verification 36
12.5 Earthquake design of the skirt 36
12.5.1 Internal forces Earthquake 36
12.5.2 Proof of strength (Ultimate limit state) 37
12.5.3 Proof of strain (Serviceability limit state) 37
12.5.4 Stability proof (Ultimate limit state) 38

13 Overlay laminate connection skirt - vessel 39
13.1 Proof of strength (Ultimate limit state) 39
13.1.1 Design value of actions 39
13.1.2 Design value of corresponding resistance 40
13.1.3 Verification 40
13.2 Proof of strain (Serviceability limit state) 40
13.2.1 Design value of actions 40
13.2.2 Limit design value of serviceability criterion 40
13.2.3 Verification 40
13.3 Seismic design of the skirt overlay 41
13.3.1 Proof of strength (Ultimate limit state) 41
13.3.2 Proof of strain (Serviceability limit state) 41

14 Analysis of the bottom 42
14.1 Influence factor A5 42
14.2 Characteristic strength values 42
14.3 Moduli of elasticity 42
14.4 Actions, which cause internal forces for the bottom 42
14.5 Strength analysis (Ultimate limit state) 42
14.5.1 Design value of actions 42
14.5.2 Proof of strain (Serviceability limit state) 44
14.5.3 Stability proof of the bottom (Ultimate limit state) 45

15 Lower part of the cylinder (Region 1) 46
15.1 Strength analysis (Ultimate limit state) 46
15.1.1 Design value of corresponding resistance 47
15.1.2 Verification 47
15.2 Proof of strain (Serviceability limit state) 47
15.2.1 Design value of actions 47
15.2.2 Limit design value of serviceability criterion 47
15.2.3 Verification 47
15.3 Earthquake design of region 1 (Ultimate limit state) 48
15.3.1 Strength analysis (Ultimate limit state) 48
15.3.2 Proof of strain (Serviceability limit state) 48

16 Upper part of the skirt (Region 2) 49
16.1 Strength analysis (Ultimate limit state) 49
16.1.1 Design value of corresponding resistance 50
16.1.2 Verification 50
16.2 Proof of strain (Serviceability limit state) 50
16.2.1 Design value of actions 50
16.2.2 Limit design value of serviceability criterion 50
16.2.3 Verification 50
16.3 Seismic design of region 2 (Ultimate limit state) 51
16.3.1 Strength analysis (Ultimate limit state) 51
16.3.2 Design value of corresponding resistance 51

16.3.3 Verification 51
16.4 Proof of strain (Serviceability limit state) 51
16.4.1 Design value of actions 51
16.4.2 Limit design value of serviceability criterion 51
16.4.3 Verification 52

17 Flange design 52

18 Anchorage 57
18.1 Anchorage for wind loads (Permanent / Transient situation) 57
18.1.1 Uplifting anchor force 57
18.1.2 Anchor shear force 57
18.2 Anchorage for seismic loads (Seismic design situation) 57
18.2.1 Uplifting anchor force 57
18.2.2 Anchor shear force 58