DIN 2413:2020-04 (E)

Seamless steel tubes for oil- and water-hydraulic systems - Calculation rule s for pipes and elbows for dynamic loads

Contents

Page

7.2.6 Circumferential bending stresses as a result of out-of-roundness 31
7.3 External pressure 31
7.4 Classification and assessment of stresses 31
7.4.1 General 31
7.4.2 Stress categories 32
7.4.3 Plastic theory 33
7.4.4 Reference stresses 33
7.4.5 Limitation of stresses 33

Bibliography 34

Figures Figure 1 -- Schematic representation of an elbow with dimensions, notation 13

Figure 2 -- Decreased fatigue strength of elbows with non-round cross-section 18

Figure 3 -- BI and BA for a known inside diameter 19

Figure 4 -- BI and BA for a known outside diameter 20

Figure 5 -- Design factor B for elbows where the wall thickness svi = sva with outside diameter = nominal diameter 21

Figure 6 -- Fatigue strength of seamless steel pipes with an outside diameter da > 114,3 mm 26

Figure 7 -- Fatigue strength of seamless steel pipes with an outside diameter da 114,3 mm, quality characteristics as in DIN EN 10216-1 or comparable standards and codes of practice 26

Tables Table 1 -- Units 6

Table 2 -- Symbols 6

Table 3 -- Determining the design wall thickness sv and test pressure p' 10

Table 4 -- Mechanical characteristics of the relevant materials 12

Table 5 -- Analysis of stress (reference stresses based on the maximum shear theory) 17

Table 6 -- Maximum number of load cycles for seamless steel pipes with an outside diameter > 114,3 mm (determined with SL = 10 as in Figure 6) 23

Table 7 -- Maximum number of load cycles for seamless steel pipes with an outside diameter 114,3 mm, quality characteristics as in DIN EN 10216-1 or comparable standards and codes of practice (determined with SL = 10 as in Figure 7) 23