

# DIN 6647-2:2020-07 (E)

## Means of packaging - Cylindrical beverage containers - Part 2: Allowable operating pressure up to 0,7 MPa, nominal volume up to 50 l

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions.....</b>	<b>4</b>
<b>4</b>	<b>Dimensions and designation .....</b>	<b>4</b>
<b>5</b>	<b>Material .....</b>	<b>6</b>
<b>6</b>	<b>Design.....</b>	<b>6</b>
<b>6.1</b>	<b>General .....</b>	<b>6</b>
<b>6.2</b>	<b>Hygiene.....</b>	<b>6</b>
<b>7</b>	<b>Requirements .....</b>	<b>6</b>
<b>7.1</b>	<b>Constancy of volume .....</b>	<b>6</b>
<b>7.2</b>	<b>Dimensional stability .....</b>	<b>7</b>
<b>7.3</b>	<b>Safety against bursting.....</b>	<b>7</b>
<b>8</b>	<b>Testing .....</b>	<b>7</b>
<b>8.1</b>	<b>General .....</b>	<b>7</b>
<b>8.2</b>	<b>Procedure .....</b>	<b>7</b>
<b>8.3</b>	<b>Constancy of volume .....</b>	<b>8</b>
<b>8.4</b>	<b>Dimensional stability.....</b>	<b>8</b>
<b>8.5</b>	<b>Pressure test.....</b>	<b>8</b>
<b>8.6</b>	<b>Hygiene.....</b>	<b>8</b>
<b>9</b>	<b>Marking .....</b>	<b>8</b>
<b>Bibliography .....</b>		<b>9</b>