

# DIN 6647-2:2020-07 (E)

## Means of packaging - Cylindrical beverage containers - Part 2: Allowable operating pressure up to 0,7 MPa, nominal volume up to 50 l

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b> <b>Scope</b> .....		4
<b>2</b> <b>Normative references</b> .....		4
<b>3</b> <b>Terms and definitions</b> .....		4
<b>4</b> <b>Dimensions and designation</b> .....		4
<b>5</b> <b>Material</b> .....		6
<b>6</b> <b>Design</b> .....		6
<b>6.1</b> <b>General</b> .....		6
<b>6.2</b> <b>Hygiene</b> .....		6
<b>7</b> <b>Requirements</b> .....		6
<b>7.1</b> <b>Constancy of volume</b> .....		6
<b>7.2</b> <b>Dimensional stability</b> .....		7
<b>7.3</b> <b>Safety against bursting</b> .....		7
<b>8</b> <b>Testing</b> .....		7
<b>8.1</b> <b>General</b> .....		7
<b>8.2</b> <b>Procedure</b> .....		7
<b>8.3</b> <b>Constancy of volume</b> .....		8
<b>8.4</b> <b>Dimensional stability</b> .....		8
<b>8.5</b> <b>Pressure test</b> .....		8
<b>8.6</b> <b>Hygiene</b> .....		8
<b>9</b> <b>Marking</b> .....		8
<b>Bibliography</b> .....		9