DIN EN 1254-6:2021-10 (E)

Copper and copper alloys - Plumbing fittings - Part 6: Push-fit fittings for use with metallic tubes, plastics and multilayer pipes

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 8

4 Product characteristics 8
4.1 Internal pressure 8
4.2 Tightness 8
4.3 Resistance to high temperature (for heating networks) 9
4.4 Release of dangerous substances 9
4.5 Durability 10
4.6 Wall thickness at threaded portions of adaptor fittings 10
4.7 Dimensions of tail pipe ends for swivel fittings 10
4.8 Threaded end dimensions 11
4.9 Other adapter ends (not defined in EN 1254-20:2021) 11
4.10 Bore dimensions 11
4.11 Identity of elastomeric sealing material 11
4.12 Tube / pipe abutment 11
4.13 Alignment of the fitting ends 11
4.14 Shapes for tightening systems 12
4.15 Surface condition 12
4.16 Disconnection and re-use (for fittings capable of being disconnected) 12
4.17 Plated or coated surfaces 12

5 Testing, assessment and sampling methods 12
5.1 General 12
5.2 Internal hydrostatic pressure test 12
5.3 Tightness 13
5.4 Durability 16
5.5 Wall thickness at threaded portions of adaptor fittings 17
5.6 Dimensions of tail pipe ends for swivel fittings 18
5.7 Threaded end dimensions 18
5.8 Bore dimensions 18
5.9 Identity of elastomeric sealing material for liquid applications 18
5.10 Alignment of the fitting ends 18
5.11 Disconnection and re-use (for fittings capable of being disconnected) 18

6 Evaluation of conformity 19
6.1 General 19
6.2 Type testing 19
6.3 Test reports 22
6.4 Factory production control (FPC) 22

7 Designation 25

8 Marking, labelling and packaging 25

8.1 General 25
8.2 Dezincification resistant copper zinc alloys 25

Annex A (normative) Operating temperatures and design pressures 26

Bibliography 28