

DIN EN 1254-4:2021-10 (E)

Copper and copper alloys - Plumbing fittings - Part 4: Threaded fittings

Contents		Page
European foreword		3
Introduction		4
1 Scope		5
2 Normative references		5
3 Terms and definitions		6
4 Product characteristics		6
4.1 Internal pressure		6
4.2 Tightness		6
4.3 Resistance to high temperature (for heating networks)		6
4.4 Release of dangerous substances		7
4.5 Durability		7
4.6 Wall thickness at threaded portions of fittings		7
4.7 Dimensions of tail pipe ends for swivel fittings		7
4.8 Dimensions of gas union connectors		8
4.9 Threaded end dimensions		8
4.10 Other adapter ends (not defined in EN 1254-20:2021)		8
4.11 Bore dimensions		8
4.12 Alignment of the fitting ends		8
4.13 Shapes for tightening systems		8
4.14 Surface condition		8
4.15 Plated or coated surfaces		8
5 Testing, assessment and sampling methods		9
5.1 General		9
5.2 Internal pressure		9
5.3 Tightness: Integrity of fabricated fitting bodies or having an 'as cast' microstructure		9
5.4 Durability		9
5.5 Wall thickness at threaded portions of adaptor fittings		10
5.6 Dimensions of tail pipe ends for swivel fittings		10
5.7 Dimensions of gas union connectors		10
5.8 Threaded end dimensions		10
5.9 Bore dimensions		10
5.10 Alignment of the fitting ends		11
6 Evaluation of conformity		11
6.1 General		11
6.2 Type testing		11
6.3 Factory production control (FPC)		13
7 Designation		15
8 Marking, labelling and packaging		15
8.1 General		15
8.2 Dezincification resistant copper zinc alloys		15
Annex A (normative) Maximum operating temperatures and maximum operating pressures		16
Bibliography		18