

DIN EN 1254-20:2021-10 (E)

Copper and copper alloys - Plumbing fittings - Part 20: Definitions, thread dimensions, test methods, reference data and supporting information

Contents		Page
European foreword		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Thread dimensions	10
4.1	Wall thickness at threaded portions of fittings	10
4.2	Dimensions of tail pipe ends for swivel fittings	11
4.3	Dimensions of gas union connectors	14
4.4	Threaded end dimensions	16
4.5	Minimum bore and cross-sectional area of fittings	22
5	Test method for leak tightness under internal hydrostatic pressure	26
5.1	Introduction	26
5.2	Principle	27
5.3	Apparatus	27
5.4	Test piece	27
5.5	Procedure	28
6	Test method for leak tightness under internal pneumatic pressure	28
6.1	Introduction	28
6.2	Principle	28
6.3	Apparatus	29
6.4	Test piece	29
6.5	Procedure	30
7	Integrity of fabricated fitting bodies or having an 'as cast' microstructure	31
7.1	Introduction	31
7.2	Principle	31
7.3	Apparatus	31
7.4	Test piece	31
7.5	Procedure	32
8	Test method for resistance to pull out of joints to metallic tubes	32
8.1	Introduction	32
8.2	Principle	32
8.3	Apparatus	32
8.4	Test assembly	33
8.5	Procedure	33
9	Test method for the resistance of joints with metallic tube to vibration	33
9.1	Introduction	33
9.2	Principle	33
9.3	Apparatus	34
9.4	Test assembly	34
9.5	Procedure	35
10	Test method for the resistance of joints to static flexural force	35

10.1	Introduction	35
10.2	Principle	35
10.3	Apparatus	35
10.4	Test piece	35
10.5	Procedure	36
11	Test method for leak tightness of joints under vacuum	37
11.1	Introduction	37
11.2	Principle	37
11.3	Apparatus	37
11.4	Test piece	38
11.5	Procedure	38
12	Test method for the resistance of joints to temperature cycling (liquid applications)	39
12.1	Introduction	39
12.2	Principle	39
12.3	Apparatus	39
12.4	Test assembly	39
12.5	Procedure	41
13	Test method for the resistance of joints to temperature cycling (fuel gas applications)	41
13.1	Introduction	41
13.2	Principle	42
13.3	Apparatus	42
13.4	Test assembly	42
13.5	Procedure	42
14	Method for detecting non-pressed fitting ends	43
14.1	Introduction	43
14.2	Principle	43
14.3	Apparatus	43
14.4	Test piece	44
14.5	Procedure	44
14.6	Results	44
15	Determination of resistance to stress corrosion	45
15.1	Introduction	45
15.2	Test piece	45
15.3	Procedure	45
15.4	Test report	45
16	Test method for detection of a carbon film on the surface of copper fittings	45
16.1	Preparation of the test piece	45
16.2	Procedure	45
16.3	Detection and assessment of films	46
17	Determination of mean depth of dezincification	46
17.1	Introduction	46
17.2	Procedure	46
17.3	Expression of results	46
18	Test method for the resistance of joints to pressure cycling	47
18.1	Introduction	47
18.2	Principle	47
18.3	Apparatus	47
18.4	Test pieces	49
18.5	Procedure	49
19	Test method for disconnection and re-use	50
19.1	Introduction	50
19.2	Principle	50
19.3	Apparatus	50

19.4	Test assembly	50
19.5	Procedure	50
20	Method for determining if the diameter and/or the length of engagement of a capillary end is/are within the specified tolerance	50
20.1	Principle	50
20.2	Apparatus	51
20.3	Test piece	55
20.4	Procedure	55
20.5	Results	55
21	Method for determining the minimum length of engagement of an integral solder or brazing ring socket having a formed groove	55
21.1	Introduction	55
21.2	Principle	55
21.3	Apparatus	56
21.4	Test piece	56
21.5	Procedure	56
21.6	Results	56
	Annex A (informative) Assembling instructions	57
	Bibliography	65