DIN EN 15266:2025-02 (E)

Stainless steel pliable corrugated tubing kits for gas installation pipework with an operating pressure up to 0,2 MPa (2 bar)

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms, definitions and abbreviations 7

4 Design requirements 9
4.1 General 9
4.2 Nominal size DN, wall thickness and pressure drop 10
4.3 Threads 10
4.4 PLT fittings 10
4.5 Seals 11
4.6 Supports 11
4.7 Electrical conductivity requirements 11
4.8 Cover 11
4.9 Additional protection 12
4.10 Environment 12

5 Performance and test requirements 12
5.1 General 12
5.2 Tightness 16
5.3 Dimensional check 17
5.4 Bending performance 17
5.5 Crushing resistance 18
5.6 Stability under pressure 20
5.7 Wear resistance of outer cover 20
5.8 Structural strength test 21
5.9 Impact resistance 21
5.10 Penetration resistance 22
5.11 Resistance to pull out 23
5.12 Chemical resistance 23
5.13 Low temperature resistance 26
5.14 Ageing 26
5.15 Tightness in case of fire 28
5.16 Reaction to fire 29
5.17 Electrical conductivity 29
5.18 Pressure drop 30
5.19 Maximum load for admissible deformation of PLT support 36
5.20 Dangerous substances 37

6 Assembly and installation instruction 38
6.1 Instructions 38
6.2 Marking, labelling and packaging 39

Annex A (normative) Single-flame source test 41

A.1 General 41

A.2 Standardized mounting and fixing 41
A.3 Test definition 41
A.4 Test duration 41

Annex B (normative) Thermal attack by a single burning item 43

Annex C (informative) Factory Production Control 44

C.1 General 44
C.2 FPC recommendations for all manufacturers 44
C.3 Manufacturer's specific FPC system recommendations 45

Bibliography 47