

DIN EN 1254-20:2025-04 (E)

Copper and copper alloys - Plumbing fittings - Part 20: Definitions, thread dimensions, test methods, reference data and supporting information (includes Amendment A1:2025)

Contents		Page
European foreword		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Thread dimensions	10
4.1	Wall thickness at threaded portions of fittings	10
4.2	Dimensions of tail pipe ends for swivel fittings	11
4.3	Dimensions of gas union connectors	13
4.4	Threaded end dimensions	14
4.5	Minimum bore and cross-sectional area of fittings	20
5	Test method for leak tightness under internal hydrostatic pressure	24
5.1	Introduction	24
5.2	Principle	25
5.3	Apparatus	25
5.4	Test piece	25
5.5	Procedure	26
6	Test method for leak tightness under internal pneumatic pressure	26
6.1	Introduction	26
6.2	Principle	26
6.3	Apparatus	27
6.4	Test piece	27
6.5	Procedure	28
7	Integrity of fabricated fitting bodies or having an 'as cast' microstructure	29
7.1	Introduction	29
7.2	Principle	29
7.3	Apparatus	29
7.4	Test piece	29
7.5	Procedure	30
8	Test method for resistance to pull out of joints to metallic tubes	30
8.1	Introduction	30
8.2	Principle	30
8.3	Apparatus	30
8.4	Test assembly	31
8.5	Procedure	31
9	Test method for the resistance of joints with metallic tube to vibration	31
9.1	Introduction	31
9.2	Principle	31
9.3	Apparatus	32
9.4	Test assembly	32
9.5	Procedure	33

10	Test method for the resistance of joints to static flexural force	33
10.1	Introduction	33
10.2	Principle	33
10.3	Apparatus	33
10.4	Test piece	33
10.5	Procedure	34
11	Test method for leak tightness of joints under vacuum	35
11.1	Introduction	35
11.2	Principle	35
11.3	Apparatus	35
11.4	Test piece	36
11.5	Procedure	36
12	Test method for the resistance of joints to temperature cycling (liquid applications)	37
12.1	Introduction	37
12.2	Principle	37
12.3	Apparatus	37
12.4	Test assembly	37
12.5	Procedure	39
13	Test method for the resistance of joints to temperature cycling (fuel gas applications)	39
13.1	Introduction	39
13.2	Principle	40
13.3	Apparatus	40
13.4	Test assembly	40
13.5	Procedure	40
14	Method for detecting non-pressed fitting ends	41
14.1	Introduction	41
14.2	Principle	41
14.3	Apparatus	41
14.4	Test piece	42
14.5	Procedure	42
14.6	Results	42
15	Determination of resistance to stress corrosion	43
15.1	Introduction	43
15.2	Test piece	43
15.3	Procedure	43
15.4	Test report	43
16	Test method for detection of a carbon film on the surface of copper fittings	43
16.1	Preparation of the test piece	43
16.2	Procedure	43
16.3	Detection and assessment of films	44
17	Determination of mean depth of dezincification	44
17.1	Introduction	44
17.2	Procedure	44
17.3	Expression of results	44
18	Test method for the resistance of joints to pressure cycling	45
18.1	Introduction	45
18.2	Principle	45
18.3	Apparatus	45
18.4	Test pieces	47
18.5	Procedure	47
19	Test method for disconnection and re-use	48
19.1	Introduction	48

19.2	Principle	48
19.3	Apparatus	48
19.4	Test assembly	48
19.5	Procedure	48
20	Method for determining if the diameter and/or the length of engagement of a capillary end is/are within the specified tolerance	48
20.1	Principle	48
20.2	Apparatus	49
20.3	Test piece	53
20.4	Procedure	53
20.5	Results	53
21	Method for determining the minimum length of engagement of an integral solder or brazing ring socket having a formed groove	53
21.1	Introduction	53
21.2	Principle	53
21.3	Apparatus	53
21.4	Test piece	54
21.5	Procedure	54
21.6	Results	54
22	"Minimum wall thickness"	55
Annex A (informative) Assembling instructions		56
Bibliography		64