

DIN 2413:2020-04 (E)

Seamless steel tubes for oil- and water-hydraulic systems - Calculation rules for pipes and elbows for dynamic loads

Contents

Page

7.2.6	Circumferential bending stresses as a result of out-of-roundness	31
7.3	External pressure	31
7.4	Classification and assessment of stresses	31
7.4.1	General	31
7.4.2	Stress categories	32
7.4.3	Plastic theory	33
7.4.4	Reference stresses	33
7.4.5	Limitation of stresses	33
Bibliography		34
Figures Figure 1 -- Schematic representation of an elbow with dimensions, notation		13
Figure 2 -- Decreased fatigue strength of elbows with non-round cross-section		18
Figure 3 -- BI and BA for a known inside diameter		19
Figure 4 -- BI and BA for a known outside diameter		20
Figure 5 -- Design factor B for elbows where the wall thickness $s_{vi} = s_{va}$ with outside diameter = nominal diameter		21
Figure 6 -- Fatigue strength of seamless steel pipes with an outside diameter $d_a > 114,3$ mm		26
Figure 7 -- Fatigue strength of seamless steel pipes with an outside diameter $d_a \leq 114,3$ mm, quality characteristics as in DIN EN 10216-1 or comparable standards and codes of practice		26
Tables Table 1 -- Units		6
Table 2 -- Symbols		6
Table 3 -- Determining the design wall thickness s_v and test pressure p'		10
Table 4 -- Mechanical characteristics of the relevant materials		12
Table 5 -- Analysis of stress (reference stresses based on the maximum shear theory)		17
Table 6 -- Maximum number of load cycles for seamless steel pipes with an outside diameter $> 114,3$ mm (determined with $SL = 10$ as in Figure 6)		23
Table 7 -- Maximum number of load cycles for seamless steel pipes with an outside diameter $\leq 114,3$ mm, quality characteristics as in DIN EN 10216-1 or comparable standards and codes of practice (determined with $SL = 10$ as in Figure 7)		23