

DIN EN ISO 14113:2014-02 (E)

Gas welding equipment - Rubber and plastics hose and hose assemblies for use with industrial gases up to 450 bar (45 M Pa) (ISO 14113:2013)

| Contents | | Page |
|---------------------|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 5 |
| 4 | Construction | 6 |
| 4.1 | Hose | 6 |
| 4.2 | End fittings | 6 |
| 4.3 | Hose assemblies | 6 |
| 5 | Dimensions and tolerances | 6 |
| 5.1 | Bore size | 6 |
| 5.2 | Concentricity | 6 |
| 5.3 | Cut lengths and tolerances | 7 |
| 5.4 | Length of hoses assemblies | 7 |
| 6 | Physical properties of lining and cover -- Type tests | 7 |
| 6.1 | General | 7 |
| 6.2 | Resistance to ignition requirement for oxygen hose lining | 8 |
| 6.3 | Resistance to acetone (acetylene hose only) | 8 |
| 7 | Performance requirements -- Type tests | 8 |
| 7.1 | Pressure resistance requirements | 8 |
| 7.2 | Adhesion (rubber hoses only) | 9 |
| 7.3 | Flexibility | 9 |
| 7.4 | Low temperature flexibility | 9 |
| 7.5 | Ozone resistance (for hoses with an outer protective cover of rubber) | 9 |
| 7.6 | UV resistance (for hoses with plastics cover) | 9 |
| 7.7 | Permeability to gas | 9 |
| 7.8 | Electrical conductivity | 9 |
| 7.9 | End fitting integrity | 9 |
| 8 | Performance requirements -- Production tests | 10 |
| 8.1 | Pressure tests for hose assemblies | 10 |
| 8.2 | Leak test | 10 |
| 8.3 | Cleaning for oxygen service | 10 |
| 9 | Marking | 10 |
| 10 | Packaging | 11 |
| 11 | Instructions | 11 |
| Annex A (normative) | Acetylene decomposition test for hose assemblies used in high pressure acetylene installations | 12 |
| Annex B (normative) | Oxygen pressure surge test | 13 |

| | |
|--|-----------|
| Annex C (normative) Oxygen system installation considerations | 15 |
| Bibliography | 16 |