

DIN EN ISO 14917:2017-08 (E)

Thermal spraying - Terminology, classification (ISO 14917:2017)

Contents

Page

| | |
|---|----|
| Foreword | 5 |
| 6.2.4 Contact tube | 23 |
| 6.2.5 Wire feed mechanism | 24 |
| 6.2.6 Powder feeder | 24 |
| 6.2.7 Powder injector | 24 |
| 6.3 Process specific terms of thermal spraying, terms | 24 |
| 6.3.1 Spray material | 24 |
| 6.3.2 Carrier gas | 24 |
| 6.3.3 Atomizing gas | 24 |
| 6.3.4 Propellant gas | 24 |
| 6.3.5 Spray jet | 24 |
| 6.3.6 Spray particles | 24 |
| 6.3.7 Splat | 24 |
| 6.3.8 Spray deposit | 24 |
| 6.3.9 Spray distance | 24 |
| 6.3.10 Spray angle | 24 |
| 6.3.11 Spray velocity | 25 |
| 6.3.12 Spray trace overlapping | 25 |
| 6.3.13 Spray spot | 25 |
| 6.3.14 Deposition rate | 25 |
| 6.3.15 Spray losses | 25 |
| 6.3.16 Deposition efficiency | 25 |
| 6.3.17 Masking | 25 |
| 6.3.18 Sealing | 25 |
| 6.3.19 Thermal treatment | 25 |
| 6.3.20 Fusing of sprayed deposits | 25 |
| 6.4 Coating specific terms | 25 |
| 6.4.1 Sprayed coating | 25 |
| 6.4.2 Substrate | 26 |
| 6.4.3 Bond coat | 26 |
| 6.4.4 Top coat | 26 |
| 6.4.5 Interface | 26 |
| 6.4.6 Non-melted particles | 26 |
| 6.4.7 Re-solidified particles | 26 |
| 6.5 Properties of thermally sprayed deposits, terms | 26 |
| 6.5.1 Tensile adhesive strength, RH | 26 |
| 6.5.2 Cohesive strength | 26 |
| 6.5.3 Hardness | 26 |
| 6.5.4 Shear load resistance | 27 |
| 6.5.5 Other properties | 27 |
| Annex A (informative) Master chart of thermal spraying processes -- Classification according to the energy carriers used for spraying | 28 |
| Annex B (informative) Keyword index | 29 |
| Bibliography | 31 |