

# ISO 9455-16:2019 (E)

## Soft soldering fluxes — Test methods — Part 16: Flux efficacy test, wetting balance method

---

### Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Principle
6	Reagents
7	Apparatus
8	Test pieces
9	Procedure
9.1	Preparation of the test pieces
9.1.1	Cleaning
9.1.2	Ageing the surface by sulfidation process
9.1.3	Steam ageing the surface
9.1.4	Damp-heat, steady-state ageing
9.2	Test method
10	Reference value using standard flux
11	Presentation of results
12	Calculation and expression of results
13	Test report
Annex A	(normative) Method for the preparation of standard rosin (colophony) based liquid fluxes having 25 % (by mass) non-volatile content
A.1	General
A.2	Principle
A.3	Apparatus
A.4	Reagents
A.5	Procedure
A.5.1	Non-activated rosin
A.5.2	Halogen-activated rosin
A.6	Storage
Annex B	(normative) Method for the production of test pieces with a controlled-contaminated surface for the wetting balance test (artificial sulfidation method)
B.1	Copper test pieces for the artificial sulfidation method
B.1.1	Reagents
B.1.2	Apparatus
B.1.3	Preparation of baths
B.1.3.1	Electrolytic copper-plating bath
B.1.3.1.1	Solution A

- B.1.3.1.2 Solution B**
- B.1.3.1.3 Electrolysis bath**
- B.1.3.2 Degreasing bath**
- B.1.3.3 Stripping bath**
- B.1.3.4 Decontamination bath**
- B.1.4 Copper plating of blanks**
- B.2 Controlled contamination**
- B.2.1 Reagents**
- B.2.2 Apparatus**
- B.2.3 Preparation of metallic strips**
- B.2.4 Preparation of solutions**
  - B.2.4.1 Preparation of solution A**
  - B.2.4.2 Standardization of solution A**
  - B.2.4.3 Preparation of solution B**
  - B.2.4.4 Preparation of sulfidization bath**
- B.2.5 Sulfidization**

Page count: 18