

# ISO 9090:2019-10 (E)

## Gas tightness of equipment for gas welding and allied processes

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Expression of leakage .....</b>	<b>1</b>
<b>5</b>	<b>Gas to be used for the tests .....</b>	<b>2</b>
<b>5.1</b>	<b>General .....</b>	<b>2</b>
<b>5.2</b>	<b>Type tests .....</b>	<b>2</b>
<b>5.3</b>	<b>Routine tests .....</b>	<b>2</b>
<b>6</b>	<b>Test pressure .....</b>	<b>2</b>
<b>6.1</b>	<b>Regulators .....</b>	<b>2</b>
<b>6.2</b>	<b>Other equipment .....</b>	<b>2</b>
<b>6.2.1</b>	<b>Type tests .....</b>	<b>2</b>
<b>6.2.2</b>	<b>Routine test .....</b>	<b>2</b>
<b>7</b>	<b>Maximum permissible external gas leakage rates at the above defined pressures .....</b>	<b>2</b>
<b>7.1</b>	<b>Regulators .....</b>	<b>2</b>
<b>7.2</b>	<b>Blowpipes .....</b>	<b>2</b>
<b>7.3</b>	<b>Safety devices .....</b>	<b>3</b>
<b>7.4</b>	<b>Quick action couplings .....</b>	<b>3</b>
<b>7.5</b>	<b>Devices with combined functions .....</b>	<b>3</b>
<b>7.6</b>	<b>Hose assembly .....</b>	<b>3</b>
<b>7.7</b>	<b>Other equipment .....</b>	<b>3</b>
<b>8</b>	<b>Measurement of the leakage rate .....</b>	<b>3</b>
<b>8.1</b>	<b>General .....</b>	<b>3</b>
<b>8.2</b>	<b>Principle of the method .....</b>	<b>3</b>
<b>8.3</b>	<b>Test apparatus for immersion method .....</b>	<b>3</b>
<b>8.4</b>	<b>Procedure .....</b>	<b>4</b>
<b>Annex A (normative)</b>	<b>Correction of measurements .....</b>	<b>5</b>
<b>Annex B (normative)</b>	<b>Test methods for blowpipes .....</b>	<b>6</b>