

ISO 14920:2023-08 (E)

Thermal spraying - Spraying and fusing of self-fluxing alloys

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Influence on the substrate and design	1
4.1	Substrate	1
4.2	Design	2
5	Spray material of the self-fluxing alloy	2
5.1	Selection	2
5.2	Composition	2
6	Preparation of the component	2
6.1	General	2
6.1.1	Surface cleanliness	2
6.1.2	Removal of prior surface treatments	2
6.1.3	Pre-machining requirements	3
6.1.4	Surface preparation requirements	3
6.2	Methods of surface preparation	3
6.2.1	Surface preparation requirements	3
6.2.2	Surface preparation inspection	3
6.2.3	General masking of surface preparation	3
6.2.4	Plug masking for surface preparation	3
6.3	Cleanliness	3
7	Spray and fusion process	4
7.1	Spraying with simultaneous fusion	4
7.1.1	Procedure	4
7.1.2	Particle size and particle size range of the powder particles	4
7.1.3	Coating thickness	4
7.2	Spraying with subsequent fusion	4
7.2.1	Procedure	4
7.2.2	Particle size and particle size range of the powder particles	4
7.2.3	Coating thickness	5
7.3	Spraying technique — Procedure	5
7.3.1	General	5
7.3.2	Preheating	5
7.3.3	Spraying	5
7.3.4	Fusing the deposit	5
7.3.5	Cooling	6
8	Final machining	6
9	Hardness testing	6
9.1	General	6
9.2	Standard hardness test	6
Annex A (informative)	Reference values for the expected hardness of the fused coating	8
Bibliography		9