

ISO 16432:2006-02 (E)

Resistance welding - Procedure for projection welding of uncoated and coated low carbon steels using embossed projection(s)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols | 2 |
| 5 | Materials | 2 |
| 5.1 | Form | 2 |
| 5.2 | Steel grades | 3 |
| 5.3 | Surface conditions | 3 |
| 6 | Component design and manufacture | 3 |
| 6.1 | Component design | 3 |
| 6.1.1 | General | 3 |
| 6.1.2 | Placement of projections | 3 |
| 6.2 | Projection dimensions | 4 |
| 6.2.1 | General | 4 |
| 6.2.2 | Dissimilar sheet thickness | 4 |
| 6.2.3 | Multi-weld arrays | 5 |
| 6.3 | Ancillary manufacturing considerations | 5 |
| 7 | Welding equipment | 5 |
| 7.1 | Welding machine | 5 |
| 7.2 | Electrode assembly (tooling) | 5 |
| 7.3 | Design of electrode assembly | 5 |
| 7.3.1 | Contact face | 5 |
| 7.3.2 | Electrode inserts | 5 |
| 7.3.3 | Electrode cooling | 6 |
| 7.3.4 | Location of components (tooling) | 6 |
| 7.3.5 | Tooling design considerations | 6 |
| 8 | Weld assessment -- Type tests | 6 |
| 8.1 | General | 6 |
| 8.2 | Test requirements | 7 |
| 8.2.1 | Weld diameter | 7 |
| 8.2.2 | Weld fracture mode | 7 |
| 8.2.3 | Weld strength | 7 |
| 8.2.4 | Visual and metallographic examination | 8 |
| 8.3 | Weld appearance -- Surface condition | 8 |
| 8.4 | Distortion | 8 |
| 9 | Weld assessment -- Routine tests | 8 |
| 9.1 | General | 8 |
| 9.2 | Frequency of testing | 9 |

| | | |
|-----------|---|-----------|
| 10 | Repair of non-conforming assemblies | 9 |
| | Annex A (informative) Recommendations for projection welding equipment | 10 |
| | Annex B (informative) Relationship between sheet thickness and projection diameter (derived from ISO 8167) | 11 |
| | Annex C (informative) Typical projection welding conditions | 12 |
| | Annex D (informative) Partial list of steel types applicable to the standard | 14 |
| | Bibliography | 15 |