

DIN EN 15520:2007-11 (E)

Thermal spraying - Recommendations for constructional design of components with thermally sprayed coatings

Contents	Page
Foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Applications and specific properties of thermally sprayed coatings	5
4 Basic rules for design of components with thermal sprayed coatings	6
5 Design of components for partial coating by thermal spraying and final machining	7
6 Machining and post-treatment of thermal sprayed coatings	7
7 Instructions for design - Symbolic representation of the sprayed coating on drawings - Test instructions in the parts list	8
8 Examples for design suitable for spraying	8
Bibliography	18
Figures Figure 1 -- Thermal spraying of plane surfaces	10
Figure 2 -- Design of rotational symmetrical parts (thermal spraying of external surfaces)	11
Figure 3 -- Design of rotationally symmetrical parts (thermal spraying of internal surfaces)	12
Figure 4a) -- Partial coating of an internal surface standard spray gun	13
Figure 4b) -- Complete coating of an internal surface with special internal spray gun	13
Figure 5a) -- Coating pulled continued around chamfered edge	13
Figure 5b) -- Coating pulled continued around rounded edge	13
Figure 6 -- Examples of design for parts avoiding excessive edge pressure	14
Figure 7 -- Example of a lift piston, parent metal: Steel EN 10088-3-1.4571 Designation of coating according to EN 14665	15
Figure 8 -- Example of a pump shaft, parent metal: Steel EN 10083-1 - C35+N	16
Tables Table 1 -- Process related features and specific properties of thermal sprayed coatings	6
Table 2 -- Basic rules and arguments	7
Table 3 -- Customary minimum dimensions for internal spraying	9
Table 4 -- Example of a parts list for finished pump shaft (see Figure 8b)	17
Bibliography	18