DIN EN 15520:2007-11 (E)

Thermal spraying - Recommendations for constructional design of components with thermally sprayed coatings

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Applications and specific properties of thermally sprayed coatings 5

4 Basic rules for design of components with thermal sprayed coatings 6

5 Design of components for partial coating by thermal spraying and final machining 7

6 Machining and post-treatment of thermal sprayed coatings 7

7 Instructions for design - Symbolic representation of the sprayed coating on drawings - Test instructions in the parts list 8

8 Examples for design suitable for spraying 8

Bibliography 18

Figures Figure 1 -- Thermal spraying of plane surfaces 10

Figure 2 -- Design of rotational symmetrical parts (thermal spraying of external surfaces) 11

Figure 3 -- Design of rotationally symmetrical parts (thermal spraying of internal surfaces) 12

Figure 4a) -- Partial coating of an internal surface standard spray gun 13

Figure 4b) -- Complete coating of an internal surface with special internal spray gun 13

Figure 5a) -- Coating pulled continued around chamfered edge 13

Figure 5b) -- Coating pulled continued around rounded edge 13

Figure 6 -- Examples of design for parts avoiding excessive edge pressure 14

Figure 7 -- Example of a lift piston, parent metal: Steel EN 10088-3-1.4571 Designation of coating according to EN 14665 15

Figure 8 -- Example of a pump shaft, parent metal: Steel EN 10083-1 - C35+N 16

Tables Table 1 -- Process related features and specific properties of thermal sprayed coatings 6

Table 2 -- Basic rules and arguments 7

Table 3 -- Customary minimum dimensions for internal spraying 9

Table 4 -- Example of a parts list for finished pump shaft (see Figure 8b) 17

Bibliography 18