

DIN EN 14034-2:2011-04 (E)

Determination of explosion characteristics of dust clouds - Part 2: Determination of the maximum rate of explosion pressure rise $(dp/dt)_{max}$ of dust clouds (includes Amendment A1:2011)

Contents		Page
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Test apparatus	7
4.1	General	7
4.2	Explosion vessel	8
4.3	Dust dispersion system (dust container, fast acting valve, connecting tube, dust disperser)	10
4.4	Ignition source	13
4.5	Control unit	13
4.6	Pressure measuring system	13
5	Dust sample	13
6	Test procedure	13
7	Calibration and verification	16
7.1	Calibration	16
7.2	Verification	16
8	Safety precautions / instructions	17
9	Alternative test equipment / procedures	17
10	Test report	18
Annex A (normative) Electro Pneumatic Valve		19
Annex B (normative) Dust dispenser with 5 mm holes		22
Annex C (normative) 20 l sphere		25
C.1	General	25
C.2	Test apparatus	25
C.3	Test conditions	26
C.4	Test procedure	26
C.5	Calculation of $(dp/dt)_{max}$, 20 l, K_{max} and K_{St}	27
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC		28
Bibliography		29

Figures Figure 1 -- 1 m³ vessel (schematic)	9
Figure 2 -- Dust container with blasting cap activated valve as commonly used for explosion suppression (schematic; it is commercially available)	10
Figure 3 -- Location of the 6 mm holes in the dust disperser	12
Figure 4 -- Dust dispersion and pressure-time curve	15
Figure 5 -- Determination of the maximum rate of explosion pressure rise (dp/dt)_{max}	16
Figure A.1 -- Electro Pneumatic Valve (schematic)	20
Figure A.2 -- Discharge characteristic of dust dispersers (without dust)	21
Figure B.1 -- Location of the 5 mm holes in the dust disperser	23
Figure B.2 -- Rebound nozzle	24
Figure B.3 -- Dispersion cup	24
Figure C.1 -- Test equipment 20 l sphere (schematic)	26
Tables Table 1 -- Maximum permissible deviations SEQ	17