DIN EN 1888:2012-06 (E)

Child care articles - Wheeled child conveyances - Safety requirements and test methods

Contents

Page

Foreword 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 General requirements and test conditions 8
4.1 Samples 8
4.2 Principle of the most onerous condition 8
4.3 Tolerances for test equipment 9
4.4 Test conditions 9
4.5 Determination of the protected volume 9
4.5.1 Protected volume of seat units 9
4.5.2 Protected volume of pram bodies having a length greater than 800 mm 11
4.5.3 Protected volume for pram bodies having a maximum internal length of 800 mm and car seats 12
4.6 Determination of the junction line 12

5 Test equipment 13
5.1 Test masses 13
5.1.1 General 13
5.1.2 Test mass A 13
5.1.3 Test mass B 14
5.1.4 Test mass C 15
5.1.5 Test mass D 16
5.1.6 Test mass D0 17
5.1.7 Test mass F 18
5.1.8 Test mass G 19
5.1.9 Test bar 20
5.2 Test probes 20
5.2.1 Finger probes 20
5.2.2 Hip probe 21
5.2.3 Large head probe 22
5.3 Angle measuring device 22
5.4 Test ball 24
5.5 Hinged board 24
5.6 Small parts cylinder 25
5.7 Bite tester 25
5.8 Test surface 27
5.9 Rectangular stops 27
5.10 Irregular surface test equipment 27
5.10.1 Obstacles 27
5.10.2 Articulating arms (see Annex B) 28

6 Chemical hazards (see A.2) 29

7 Thermal hazards (see A.3) 29

8 Mechanical hazards (see A.4) 29

8.1 Protective function (see A.4.2) 29
8.1.1 Suitability of vehicle 29
8.1.2 Minimum internal height of pram body 33
8.1.3 Restraint system and fasteners 34
8.2 Entrapment hazards (see A.4.3) 37
8.2.1 Holes and openings 37
8.2.2 Entrapment between the handle and the pram body 38
8.3 Hazards from moving parts (see A.4.4) 38
8.3.1 Requirements 38
8.3.2 Wheels 38
8.3.3 Locking mechanism(s) 39
8.4 Entanglement hazards (see A.5) 42
8.5 Choking and ingestion hazards (see A.6) 43
8.5.1 Requirements 43
8.5.2 Test methods 43
8.6 Suffocation hazards (see A.7) 44
8.6.1 Internal lining of the pram body and seat unit 44
8.6.2 Plastic packaging 44
8.7 Hazardous edges and protrusions (see A.8) 45
8.8 Parking and braking devices (see A.9) 45
8.8.1 Requirements 45
8.8.2 Test methods 46
8.9 Stability (see A.10) 49
8.9.1 Stability of vehicle 49
8.9.2 Longitudinal stability of a pram body with carrying handles 53
8.10 Structural integrity (see A.11) 54
8.10.1 Carrying handles and handle anchorage points of pram bodies and detachable seat units 54
8.10.2 Strength and durability of attachment devices for pram bodies or seat units or car seats 54
8.10.3 Irregular surface test 55
8.10.4 Dynamic strength 56
8.10.5 Wheel strength 58
8.10.6 Handle strength 59

9 Durability of marking 62

10 Product information 62
10.1 General 62
10.2 Marking of product 62
10.3 Purchase information 63
10.4 Instructions for use 64

Annex A (informative) Rationales 66

A.1 General 66
A.2 Chemical hazards (see Clause 6) 66
A.3 Thermal hazards (see Clause 7) 66
A.4 Mechanical hazards (see Clause 8) 66
A.4.1 General 66
A.4.2 Protective function (see 8.1) 66
A.4.3 Entrapment hazards (see 8.2) 66
A.4.4 Hazards from moving parts (see 8.3) 67
A.5 Entanglement hazards (see 8.4) 67
A.6 Choking and ingestion hazards (see 8.5) 67
A.7 Suffocation hazards (see 8.6) 67
A.8 Hazardous edges and protrusions (see 8.7) 67
A.9 Parking and braking devices (see 8.8) 68
A.10 Stability (see 8.9) 68
A.11 Structural integrity (see 8.10) 68

Annex B (informative) Examples of articulated arms to maintain the vehicle on the rig for the irregular surface test 69

Annex C (informative) Guideline for the application of 8.3.3.1.1.3 "Unintentional release of locking mechanism(s)" 70

C.1 Relevant definitions 70
C.2 Guidelines for the application of 8.3.3.1.1.3 "Unintentional release of locking mechanism(s)" 70
C.2.1 General 70
C.2.2 Products fitted with one single operating device (products that may be fold using only one hand) 70
C.2.3 Products fitted with two operating devices 71
C.2.4 Products having three or more operating devices 72
C.2.5 Products covered by different requirements 73

Annex D (informative) A-deviation 74

Bibliography 75