

ISO 14382:2012-12 (E)

Workplace atmospheres - Determination of toluene diisocyanate vapours using 1-(2-pyridyl)piperazine-coated glass fibre filters and analysis by high performance liquid chromatography with ultraviolet and fluorescence detectors

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Principle	1
4	Reagents and materials	2
5	Reagent solutions	2
5.1	Preparation of TDI urea derivatives	2
5.2	Analytical standards	2
5.3	Filter extraction solution	3
5.4	1-2PP filter coating solution	3
5.5	HPLC mobile phase	3
6	Apparatus	3
6.1	Air sampler	3
6.2	Sampling pump	4
6.3	Sampling pump calibration	4
6.4	Tubing	4
6.5	Flowmeter	4
6.6	Liquid chromatography system	4
7	Air sampling	5
7.1	Calibration of sampling pump	5
7.2	Safety practices	5
7.3	Preparation of air sampler	5
7.4	Collection of air samples	5
7.5	Blanks	5
7.6	Sample shipment	5
8	HPLC analysis	6
8.1	Safety precautions	6
8.2	Sample preparation	6
8.3	Standards preparation	6
8.4	HPLC conditions	6
9	Analysis	7
9.1	Calibration	7
10	Quality control	7
11	Sample quantification	7
11.1	Determination of TDI mass per sample	7
11.2	Determination of TDI mass concentration in air	8

11.3	Determination of TDI volume fraction in air	8
12	Interferences	8
13	Determination of performance characteristics	9
13.1	Introduction	9
13.2	Relevant uncertainty contributions and criteria	10
13.3	Assessment of performance characteristics (ISO GUM approach)	10
Annex A (informative) Performance characteristics		18
Bibliography		20