

# ISO 14382:2012-12 (E)

## Workplace atmospheres - Determination of toluene diisocyanate vapours using 1-(2-pyridyl)piperazine-coated glass fibre filters and analysis by high performance liquid chromatography with ultraviolet and fluorescence detectors

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Principle .....	1
4	Reagents and materials .....	2
5	Reagent solutions .....	2
5.1	Preparation of TDI urea derivatives .....	2
5.2	Analytical standards .....	2
5.3	Filter extraction solution .....	3
5.4	1-2PP filter coating solution .....	3
5.5	HPLC mobile phase .....	3
6	Apparatus .....	3
6.1	Air sampler .....	3
6.2	Sampling pump .....	4
6.3	Sampling pump calibration .....	4
6.4	Tubing .....	4
6.5	Flowmeter .....	4
6.6	Liquid chromatography system .....	4
7	Air sampling .....	5
7.1	Calibration of sampling pump .....	5
7.2	Safety practices .....	5
7.3	Preparation of air sampler .....	5
7.4	Collection of air samples .....	5
7.5	Blanks .....	5
7.6	Sample shipment .....	5
8	HPLC analysis .....	6
8.1	Safety precautions .....	6
8.2	Sample preparation .....	6
8.3	Standards preparation .....	6
8.4	HPLC conditions .....	6
9	Analysis .....	7
9.1	Calibration .....	7
10	Quality control .....	7
11	Sample quantification .....	7
11.1	Determination of TDI mass per sample .....	7
11.2	Determination of TDI mass concentration in air .....	8

11.3	Determination of TDI volume fraction in air .....	8
12	Interferences .....	8
13	Determination of performance characteristics .....	9
13.1	Introduction .....	9
13.2	Relevant uncertainty contributions and criteria .....	10
13.3	Assessment of performance characteristics (ISO GUM approach) .....	10
	Annex A (informative) Performance characteristics .....	18
	Bibliography .....	20