

ISO 16258-1:2015-09 (E)

Workplace air - Analysis of respirable crystalline silica by X-ray diffraction - Part 1: Direct-on-filter method

Contents	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 General definitions	1
3.2 Sampling definitions	2
3.3 Analytical definitions	3
3.4 Statistical terms	4
4 Principle	5
5 Sampling	5
5.1 Sampling equipment	6
5.1.1 Samplers	6
5.1.2 Filters	6
5.1.3 Sampling pumps	7
5.1.4 Flow meters	7
5.1.5 Other equipment required	7
5.2 Sample collection	8
5.3 Transport	9
6 Analytical procedure	9
6.1 Apparatus and equipment	9
6.1.1 X-ray diffraction system	9
6.1.2 Balance	9
6.1.3 Dust cloud generator	9
6.1.4 Standard reference materials	10
6.1.5 Reagents	10
6.1.6 Drift correction sample	11
6.2 Gravimetric analysis for respirable dust	11
6.3 X-ray diffraction analysis	11
6.3.1 Instrumental parameters	11
6.3.2 Scan parameters	11
6.4 Calibration curve	11
6.5 Sample treatment	13
6.6 Sample analysis	13
7 Calculation	13
7.1 Gravimetric analysis	13
7.2 X-ray diffraction analysis	13
7.3 Concentration of RCS	14
8 Performance characteristics	15
8.1 Limit of detection	15
8.2 Minimum detectable value	15
8.3 Limits of quantification	15

8.4	Uncertainty	15
8.5	Differences between samplers	16
8.6	Differences between analytical approaches	16
9	Test report	16
Annex A (informative) Example instrumental conditions		18
Annex B (informative) Data collection parameters		19
Annex C (normative) Corrections for absorption		20
Annex D (informative) Range of typical detection limits		22
Annex E (informative) Typical expanded uncertainty for the direct-on-filter method		23
Annex F (informative) Differences between samplers		24
Bibliography		25