ISO 16258-1:2015-09 (E)

Workplace air - Analysis of respirable crystalline silica by X-ray diffraction - Part 1: Direct-on-filter method

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1
3.1 General definitions 1
3.2 Sampling definitions 2
3.3 Analytical definitions 3
3.4 Statistical terms 4

4 Principle 5

5 Sampling 5
5.1 Sampling equipment 6
5.1.1 Samplers 6
5.1.2 Filters 6
5.1.3 Sampling pumps 7
5.1.4 Flow meters 7
5.1.5 Other equipment required 7
5.2 Sample collection 8
5.3 Transport 9

6 Analytical procedure 9
6.1 Apparatus and equipment 9
6.1.1 X-ray diffraction system 9
6.1.2 Balance 9
6.1.3 Dust cloud generator 9
6.1.4 Standard reference materials 10
6.1.5 Reagents 10
6.1.6 Drift correction sample 11
6.2 Gravimetric analysis for respirable dust 11
6.3 X-ray diffraction analysis 11
6.3.1 Instrumental parameters 11
6.3.2 Scan parameters 11
6.4 Calibration curve 11
6.5 Sample treatment 13
6.6 Sample analysis 13

7 Calculation 13
7.1 Gravimetric analysis 13
7.2 X-ray diffraction analysis 13
7.3 Concentration of RCS 14

8 Performance characteristics 15
8.1 Limit of detection 15
8.2 Minimum detectable value 15
8.3 Limits of quantification 15

8.4 Uncertainty 15
8.5 Differences between samplers 16
8.6 Differences between analytical approaches 16

9 Test report 16

Annex A (informative) Example instrumental conditions 18

Annex B (informative) Data collection parameters 19

Annex C (normative) Corrections for absorption 20

Annex D (informative) Range of typical detection limits 22

Annex E (informative) Typical expanded uncertainty for the direct-on-filter method 23

Annex F (informative) Differences between samplers 24

Bibliography 25