DIN EN 1888-1:2019-05 (E)

Child use and care articles - Wheeled child conveyances - Part 1: Pushchairs and prams

Contents

Page

European foreword 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 General requirements and test conditions 9
4.1 Samples 9
4.2 Principle of the most onerous condition 9
4.3 Tolerances for test equipment 9
4.4 Test conditions 10
4.5 Determination of the protected volume 10
4.5.1 Protected volume of seat units 10
4.5.2 Protected volume of pram bodies having a length greater than 800 mm 12
4.5.3 Protected volume for pram bodies having a maximum internal length of 800 mm and car seats 13
4.6 Determination of the junction line 13
4.7 Determination of the occupant space 14
4.7.1 Determination of occupant space for seat unit and car seat 14
4.7.2 Determination of occupant space for pram body having a length less than 800 mm 14
4.7.3 Determination of occupant space for pram body having a length greater than 800 mm 14

5 Test equipment 15
5.1 Test masses 15
5.1.1 General 15
5.1.2 Test mass A 15
5.1.3 Test mass B 16
5.1.4 Test mass C 16
5.1.5 Test mass D 17
5.1.6 Test mass D0 18
5.1.7 Test mass F 18
5.1.8 Test mass G 19
5.1.9 Test bar 20
5.2 Test probes 21
5.2.1 Finger probes 21
5.2.2 Hip probe 22
5.2.3 Large head probe 23
5.2.4 Conical probes 24
5.3 Angle measuring device 24
5.4 Test ball 26
5.5 Hinged board 26
5.6 Small parts cylinder 26
5.7 Bite tester 27
5.8 Test surface 28
5.9 Rectangular stops 28
5.10 Irregular surface test equipment 29
5.10.1 Obstacles 29
5.10.2 Articulating arms (see Annex B) 30

6 Chemical hazards (see A.2) 30

7 Thermal hazards (see A.3) 31

8 Mechanical hazards (see A.4) 32
8.1 Protective function (see A.4.2) 32
8.1.1 Suitability of vehicle 32
8.1.2 Minimum internal height of pram body 34
8.1.3 Restraint system and fasteners 36
8.2 Entrapment hazards (see A.4.3) 39
8.2.1 Holes and openings 39
8.2.2 Entrapment between the handle and the pram body 39
8.3 Hazards from moving parts (see A.4.4) 39
8.3.1 General 39
8.3.2 Shearing hazards (see A.4.4) 40
8.3.3 Crushing hazards, requirement (see A.4.4) 40
8.3.4 Wheels 41
8.3.5 Locking mechanism(s) 41
8.4 Entanglement hazards (see A.5) 44
8.4.1 Requirements 44
8.4.2 Test method 45
8.5 Choking and ingestion hazards (see A.6) 45
8.5.1 Requirements 45
8.5.2 Test methods 46
8.6 Suffocation hazards (see A.7) 47
8.6.1 Internal lining of the pram body and seat unit 47
8.6.2 Plastic packaging 47
8.7 Hazardous edges and protrusions (see A.8) 47
8.8 Parking and braking devices (see A.9) 48
8.8.1 Requirements 48
8.8.2 Test methods 48
8.9 Stability (see A.10) 52
8.9.1 Stability of vehicle 52
8.9.2 Longitudinal stability of a pram body with carrying handles 56
8.9.3 Stability hazards due to the position of swivelling wheels 56
8.10 Structural integrity (see A.11) 57
8.10.1 Carrying handles and handle anchorage points of pram bodies and detachable seat units 57
8.10.2 Strength and durability of attachment devices for pram bodies or seat units or car seats 57
8.10.3 Irregular surface test 58
8.10.4 Dynamic strength 59
8.10.5 Wheel strength 61
8.10.6 Handle strength 61

9 Durability of marking 65

10 Product information 65
10.1 General 65
10.2 Marking of product 65
10.3 Purchase information (A.12) 66
10.4 Instructions for use 67

Annex A (informative) Rationales 69

A.1 General 69
A.2 Chemical hazards (see Clause 6) 69
A.3 Thermal hazards (see Clause 7) 69
A.4 Mechanical hazards (see Clause 8) 69
A.4.1 General 69
A.4.2 Protective function (see 8.1) 69
A.4.3 Entrapment hazards (see 8.2) 69

A.4.4 Hazards from moving parts (see 8.3) 70
A.5 Entanglement hazards (see 8.4) 71
A.6 Choking and ingestion hazards (see 8.5) 72
A.7 Suffocation hazards (see 8.6) 72
A.8 Hazardous edges and protrusions (see 8.7) 72
A.9 Parking and braking devices (see 8.8) 72
A.10 Stability (see 8.9) 72
A.11 Structural integrity (see 8.10) 72
A.12 Purchase information (see 10.3) 73

Annex B (informative) Examples of articulated arms to maintain the vehicle on the rig for the irregular surface test 74

Annex C (informative) Guideline for the application of 8.3.5.1.1.3 "Unintentional release of locking mechanism(s)" 76

C.1 Relevant definitions 76
C.2 Guidelines for the application of 8.3.5.1.1.3 "Unintentional release of locking mechanism(s)" 76
C.2.1 General 76
C.2.2 Products fitted with one single operating device (products that may be fold using only one hand) 76
C.2.3 Products fitted with two operating devices 77
C.2.4 Products having three or more operating devices 78
C.2.5 Products covered by different requirements 78

Annex D (informative) Examples of moving parts of the canopies inside 100 mm from the pivot point 80

D.1 Case A 80
D.2 Case B 81
D.3 Case C 82

Annex E (informative) Translation of Warnings in different European languages 83

Annex F (informative) A-deviations 109

Annex G (informative) Child restraint systems: arrangement of approval marks 110

Bibliography 111