

# ISO 21832:2018 (E)

## Workplace air — Metals and metalloids in airborne particles — Requirements for evaluation of measuring procedures

---

### Contents

|           |  |
|-----------|--|
|           | Foreword   |
|           | Introduction   |
| 1         | Scope  |
| 2         | Normative references   |
| 3         | Terms and definitions  |
| 4         | Principle  |
| 5         | Requirements   |
| 5.1       | Method description   |
| 5.1.1     | Application range  |
| 5.1.2     | Method performance   |
| 5.1.3     | Safety information   |
| 5.1.4     | Samplers   |
| 5.1.5     | Sampling pumps   |
| 5.1.6     | Other requirements   |
| 5.2       | Performance requirements   |
| 5.2.1     | Limit of quantification (LOQ)  |
| 5.2.2     | Analytical recovery  |
| 5.2.3     | Expanded uncertainty   |
| 6         | Reagents and materials   |
| 6.1       | Reagents   |
| 6.2       | Standard solutions   |
| 6.3       | Test materials   |
| 6.4       | Reference air samples  |
| 7         | Apparatus  |
| 8         | Test methods   |
| 8.1       | LOD and LOQ  |
| 8.1.1     | Instrumental detection limit (IDL)   |
| 8.1.2     | Method LOD and LOQ   |
| 8.2       | Analytical recovery  |
| 8.2.1     | General  |
| 8.2.2     | Measuring procedures for soluble compounds of metals and metalloids                  |
| 8.2.2.1   | Measuring procedures that incorporate a design-based sample dissolution method       |
| 8.2.2.2   | Other measuring procedures   |
| 8.2.3     | Measuring procedures for total metals and metalloids that involve sample dissolution |
| 8.2.3.1   | Determination of analytical recovery using pure compounds                            |
| 8.2.3.2   | Determination of analytical recovery using reference materials                       |
| 8.2.3.3   | Determination of analytical recovery using reference air samples                     |
| 8.2.3.4   | Comparison of results with the acceptance criteria                                   |
| 8.2.4     | Measuring procedures that do not involve sample dissolution                          |
| 8.2.4.1   | Experimental determination of analytical recovery                                    |
| 8.2.4.1.1 | Reference air samples  |
| 8.2.4.1.2 | Workplace air samples  |
| 8.2.4.1.3 | Comparison of results with the acceptance criteria                                   |
| 8.2.4.2   | Theoretical estimation of analytical recovery  |

|           |  |
|-----------|--|
| 8.3       | Measurement uncertainty  |
| 8.3.1     | Identification of random and non-random uncertainty components                                 |
| 8.3.2     | Estimation of individual uncertainty components  |
| 8.3.2.1   | General  |
| 8.3.2.2   | Uncertainty associated with sampled air volume   |
| 8.3.2.3   | Uncertainty associated with sampling efficiency  |
| 8.3.2.4   | Uncertainty associated with sample storage and transportation                                  |
| 8.3.2.5   | Uncertainty associated with analytical recovery  |
| 8.3.2.6   | Uncertainty associated with analytical variability   |
| 8.3.3     | Calculation of expanded uncertainty  |
| 9         | Test report  |
| Annex A   | (informative) Guidance on determination of analytical recovery                                 |
| A.1       | Procedures for soluble compounds of metals and metalloids                                      |
| A.2       | Procedures that involve sample dissolution   |
| A.3       | Procedures that do not involve sample dissolution  |
| Annex B   | (informative) Experiments for method validation  |
| Annex C   | (informative) Estimation of uncertainty of measurement   |
| C.1       | General  |
| C.2       | Uncertainty associated with sampled air volume   |
| C.3       | Uncertainty associated with sampling efficiency  |
| C.3.1     | General  |
| C.3.2     | Uncertainty for aerosol samplers tested in accordance with the EN 13205-2 method               |
| C.3.2.1   | Principle  |
| C.3.2.2   | Sources of uncertainty for sampling efficiency   |
| C.3.2.3   | Calibration of sampler test system   |
| C.3.2.4   | Estimation of sampled aerosol concentration  |
| C.3.2.5   | Bias relative to the sampling convention   |
| C.3.2.6   | Flow excursion from the nominal flow rate (for respirable samplers and thoracic samplers)      |
| C.3.2.7   | Individual sampler variability (for respirable samplers and thoracic samplers)                 |
| C.3.3     | Uncertainty for aerosol samplers tested in accordance with the EN 13205-4 method               |
| C.3.3.1   | Principle  |
| C.3.3.2   | Sources of uncertainty for sampling efficiency   |
| C.3.3.3   | Test aerosol (reference) concentration, as determined using the validated reference sampler(s) |
| C.3.3.4   | Reference sampler  |
| C.3.3.5   | Sampler bias   |
| C.3.3.6   | Individual sampler variability (for respirable samplers and thoracic samplers)                 |
| C.3.3.7   | Flow excursion from the nominal flow rate (for respirable samplers and thoracic samplers)      |
| C.3.4     | Uncertainty for aerosol samplers   |
| C.3.4.1   | Inhalable samplers   |
| C.3.4.1.1 | Experimental data  |
| C.3.4.1.2 | Estimates for general use  |
| C.3.4.2   | Respirable samplers  |
| C.3.4.2.1 | Experimental data  |
| C.3.4.2.2 | Estimates for general use  |
| C.3.5     | Efficiency of collection substrate   |
| C.3.5.1   | Filter materials   |
| C.3.5.2   | Foams  |
| C.4       | Uncertainty associated with sample storage and transportation                                  |
| C.4.1     | Sample storage   |
| C.4.2     | Transportation   |
| C.5       | Uncertainty associated with analytical recovery  |
| C.5.1     | General  |
| C.5.2     | Analysis of certified reference materials and/or pure compounds                                |
| C.5.3     | Interlaboratory comparisons  |
| C.5.4     | Analysis of spiked collection substrates   |
| C.5.5     | Acceptable bias range  |
| C.5.6     | Procedures that incorporate a design-based sample preparation method                           |

- C.6      **Uncertainty associated with analytical variability**
- C.6.1    **General**
- C.6.2    **Range of sample loadings at which the analytical variability has to be estimated**
- C.6.3    **Estimation using repeatability data**
- C.6.3.1   **Analytical precision**
- C.6.3.1.1 **Estimation from data obtained from the analysis of spiked collection substrates**
- C.6.3.1.2 **Estimation from data obtained by interpolation of standard deviation**
- C.6.3.1.3 **Estimation from theory**
- C.6.3.2   **Calibration standards**
- C.6.3.2.1 **Commercial stock standard solutions**
- C.6.3.2.2 **Custom-made stock standard solutions**
- C.6.3.2.3 **Reference air samples**
- C.6.3.3   **Calibration function**
- C.6.3.4   **Dilution of sample solutions (if applicable)**
- C.6.3.5   **Instrument response drift**
- C.6.4    **Estimation using laboratory reproducibility data**
- C.6.4.1   **Analytical precision**
- C.6.4.2   **Concentration of calibration standards**
- C.6.4.3   **Calibration function**
- C.6.4.4   **Dilution of the sample solutions (if applicable)**
- C.6.4.5   **Instrument response drift**
- C.6.5    **Blank subtraction**
- C.6.5.1   **General**
- C.6.5.2   **Recalculating of analytical precision to include the random uncertainty associated with blank subtraction**
- C.6.5.3   **Non-random uncertainty component associated with no blank subtraction**
- C.7      **Calculation of combined uncertainty**
- C.7.1    **Random and non-random components of sampling and analytical uncertainty**
- C.7.2    **Random and non-random uncertainty of the measuring procedure**
- C.7.3    **Combined standard uncertainty of the measuring procedure**
- C.8      **Calculation of expanded uncertainty**

**Annex D (informative) Interpolation of standard deviation**

**Annex E (informative) Example for estimation of expanded uncertainty**

**Page count: 37**