

DIN EN 17199-4:2020-02 (E)

Workplace exposure - Measurement of dustiness of bulk materials that contain or release respirable NOAA or other respirable particles - Part 4: Small rotating drum method

Contents	Page
European foreword.....	4
Introduction	5
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions	7
4 Symbols and abbreviations	7
5 Principle	8
6 Equipment	10
6.1 General.....	10
6.2 Test apparatus.....	10
7 Requirements	13
7.1 General.....	13
7.2 Engineering control measures	14
7.3 Conditioning of the test material.....	14
7.4 Conditioning of the test equipment.....	14
8 Preparation	14
8.1 Weighing of filters.....	14
8.2 Test sample	14
8.3 Moisture content of the test material	15
8.4 Bulk density of the test material	15
8.5 Preparation of test apparatus	15
8.6 Aerosol instruments and aerosol samplers.....	15
9 Test procedure	16
9.1 General.....	16
9.2 Test sequence for running a dustiness test	17
9.3 Selection of the amount to be used for SRD dustiness triple test	18
9.3.1 General.....	18
9.3.2 Selection of 6 g test material.....	19
9.3.3 Selection of more than 6 g test material	19
9.3.4 Selection of less than 6 g test material	20
9.4 Cleaning in between runs.....	20
9.5 Cleaning of equipment after conclusion of a dustiness test	21
10 Evaluation of data	21
10.1 Respirable dustiness mass fraction.....	21
10.2 Use of CPC data.....	21
10.2.1 General.....	21
10.2.2 Number-based emission rate.....	22
10.2.3 Number-based dustiness index.....	22
10.2.4 Dustiness kinetics	23
10.2.5 Time needed to reach 50 % of the released number of particles during the test	23
10.3 Use of ELPI® data	23
10.3.1 General.....	23

10.3.2	Modal aerodynamic equivalent diameters obtained by ELPI® (aerodynamic D_p, μm)	23
10.4	Morphology and chemical characterization of the particles	24
11	Test report	24
Annex A (informative)	Example of a small rotating drum set-up	26
Bibliography		27