ISO 13855:2024-11 (E)

Safety of machinery - Positioning of safeguards with respect to the approach of the human body

Contents

Page

Foreword v

Introduction vii

1 Scope 1

2 Normative references 2

3 Terms,definitions,symbolsandabbreviatedterms 2
3.1 Terms and definitions 2
3.2 Symbols and abbreviated terms 5
3.2.1 Symbols 5
3.2.2 Abbreviated terms 5

4 Methodology 6
4.1 General 6
4.2 Static and dynamic separation distances 8
4.3 Reference planes 8
4.4 Assumptions 10
4.5 Specific requirements for ESPE regarding whole body access 11
4.5.1 General 11
4.5.2 Additional requirements for detection zones mounted vertical to the reference plane 11
4.5.3 Additional requirements for single beam devices 12
4.6 Reaching distance to SRMCD 12
4.7 Direction of approach toward detection zone of SPE 12
4.8 Speed and separation control (SSC) 13

5 Separation distance 13
5.1 General 13
5.2 Separation distance S 14
5.3 Approach speed K 14
5.3.1 Approach speed of the human body 14
5.3.2 Approach speed of mobile machinery 14
5.4 Overall system response time T 15
5.5 Reaching distance factors associated with a protective device DDS 17
5.5.1 General 17
5.5.2 Reaching distance in applications initiating a safety function 17
5.5.3 Reaching distance in applications where hazard zones can be reached by circumventing the safeguard 17
5.6 Supplemental distance factors 18

6 Dynamic separation distance 18
6.1 General 18
6.2 Dynamic separation distance for unknown human direction of approach 19
6.3 Dynamic separation distance for known human direction of approach 20

7 Consideration of the direction of approach to a detection zone 22

8 Orthogonalapproachtoadetectionzone 23
8.1 Determination of the reaching distance for an orthogonal approach to a detection zone 23
8.2 Reaching over a vertical detection zone 25
8.2.1 General 25

8.2.2 Vertical detection zones without additional protective structures 25
8.2.3 Vertical detection zones with additional protective structures 27
8.3 Reaching through a vertical detection zone 27
8.3.1 General 27
8.3.2 Reaching through a vertical detection zone with effective detection capability de 40 mm 28
8.3.3 Reaching through a vertical detection zone with effective detection capability 40 mm < de 55 mm 29
8.3.4 Reaching through a vertical detection zone with effective detection capability 55 mm < de 120 mm 29
8.3.5 Reaching through a vertical detection zone with effective detection capability de > 120 mm or undefined 30
8.3.6 Indirect approach -- Path restricted by obstacles 31
8.4 Reaching under a vertical detection zone 33
8.4.1 General 33
8.4.2 Reaching under a vertical detection zone with (de + HDB) 40 mm 34
8.4.3 Reaching under a vertical detection zone with height of the lower edge from the reference plane 40 mm < de + HDB and HDB 300 mm 34
8.4.4 Reaching under a vertical detection zone with additional protective structures 35
8.5 Single beam applications 36
8.6 Cycle re-initiation of machine operation employing active opto-electronic protective devices (AOPDs) with control function 36

9 Parallelapproachtoadetectionzone 37
9.1 General 37
9.2 Height of a detection zone for a parallel approach 37
9.3 Separation distance of a detection zone for a parallel approach 39
9.4 Depth of a detection zone for a parallel approach 39

10 Two-handcontroldevices 40
10.1 Two-hand control devices not preventing encroachment 40
10.2 Two-hand control devices preventing encroachment 41

11 Singlecontroldevices 41
11.1 Hand-operated single control devices 41
11.2 Foot-operated single control devices 42

12 Interlockingguards 43
12.1 General 43
12.2 Interlocking devices without guard locking 43
12.2.1 General 43
12.2.2 Calculation of the opening e for an interlocking guard with an interlocking device with rotary cam actuated position switch 45
12.3 Interlocking devices with guard locking 46

Annex A (informative)Achievingintendedriskreduction 48

Annex B (informative)Measurementandcalculationofsystemperformancetoachievethe intendedriskreduction 49

Annex C (normative) Devices with multiple beams or arrangements of single beams with effectivedetectioncapabilityde>120mmorundefined--Numberofbeamsandtheir heightabovethereferenceplanewithoutchangeinelevation 52

Annex D (normative)Supplierinformationfortimeanddistancetoachievetheintendedrisk reduction 54

Annex E (informative)Variablekeyfordeterminingseparationdistanceforsafeguards 55

Annex F (normative)Timefactorsintheoverallsystemresponsetimetoachievetheintended riskreduction 64

Annex G (informative)Explanationsoftheformulaeandvaluesusedwithinthisdocument 67

Bibliography 71