

DIN EN ISO 13855:2025-10 (E)

Safety of machinery - Positioning of safeguards with respect to the approach of the human body (ISO 13855:2024)

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | v |
| Introduction | | vii |
| 1 | Scope | 1 |
| 2 | Normative references | 2 |
| 3 | Terms, definitions, symbols and abbreviated terms | 2 |
| 3.1 | Terms and definitions | 2 |
| 3.2 | Symbols and abbreviated terms | 5 |
| 3.2.1 | Symbols | 5 |
| 3.2.2 | Abbreviated terms | 5 |
| 4 | Methodology | 6 |
| 4.1 | General | 6 |
| 4.2 | Static and dynamic separation distances | 8 |
| 4.3 | Reference planes | 8 |
| 4.4 | Assumptions | 10 |
| 4.5 | Specific requirements for ESPE regarding whole body access | 11 |
| 4.5.1 | General | 11 |
| 4.5.2 | Additional requirements for detection zones mounted vertical to the reference plane | 11 |
| 4.5.3 | Additional requirements for single beam devices | 12 |
| 4.6 | Reaching distance to SRMCD | 12 |
| 4.7 | Direction of approach toward detection zone of SPE | 12 |
| 4.8 | Speed and separation control (SSC) | 13 |
| 5 | Separation distance | 13 |
| 5.1 | General | 13 |
| 5.2 | Separation distance S | 14 |
| 5.3 | Approach speed K | 14 |
| 5.3.1 | Approach speed of the human body | 14 |
| 5.3.2 | Approach speed of mobile machinery | 14 |
| 5.4 | Overall system response time T | 15 |
| 5.5 | Reaching distance factors associated with a protective device D_{DS} | 17 |
| 5.5.1 | General | 17 |
| 5.5.2 | Reaching distance in applications initiating a safety function | 17 |
| 5.5.3 | Reaching distance in applications where hazard zones can be reached by circumventing the safeguard | 17 |
| 5.6 | Supplemental distance factors | 18 |
| 6 | Dynamic separation distance | 18 |
| 6.1 | General | 18 |
| 6.2 | Dynamic separation distance for unknown human direction of approach | 19 |
| 6.3 | Dynamic separation distance for known human direction of approach | 20 |
| 7 | Consideration of the direction of approach to a detection zone | 22 |
| 8 | Orthogonal approach to a detection zone | 23 |
| 8.1 | Determination of the reaching distance for an orthogonal approach to a detection zone | 23 |
| 8.2 | Reaching over a vertical detection zone | 25 |
| 8.2.1 | General | 25 |
| 8.2.2 | Vertical detection zones without additional protective structures | 25 |
| 8.2.3 | Vertical detection zones with additional protective structures | 27 |

| | | |
|---------------------|--|-----------|
| 8.3 | Reaching through a vertical detection zone..... | 27 |
| 8.3.1 | General..... | 27 |
| 8.3.2 | Reaching through a vertical detection zone with effective detection capability $d_e \leq 40$ mm..... | 28 |
| 8.3.3 | Reaching through a vertical detection zone with effective detection capability 40 mm < $d_e \leq 55$ mm..... | 29 |
| 8.3.4 | Reaching through a vertical detection zone with effective detection capability 55 mm < $d_e \leq 120$ mm..... | 29 |
| 8.3.5 | Reaching through a vertical detection zone with effective detection capability $d_e > 120$ mm or undefined..... | 30 |
| 8.3.6 | Indirect approach — Path restricted by obstacles..... | 31 |
| 8.4 | Reaching under a vertical detection zone..... | 33 |
| 8.4.1 | General..... | 33 |
| 8.4.2 | Reaching under a vertical detection zone with $(d_e + H_{DB}) \leq 40$ mm..... | 34 |
| 8.4.3 | Reaching under a vertical detection zone with height of the lower edge from the reference plane 40 mm < $d_e + H_{DB}$ and $H_{DB} \leq 300$ mm..... | 34 |
| 8.4.4 | Reaching under a vertical detection zone with additional protective structures..... | 35 |
| 8.5 | Single beam applications..... | 36 |
| 8.6 | Cycle re-initiation of machine operation employing active opto-electronic protective devices (AOPDs) with control function..... | 36 |
| 9 | Parallel approach to a detection zone..... | 37 |
| 9.1 | General..... | 37 |
| 9.2 | Height of a detection zone for a parallel approach..... | 37 |
| 9.3 | Separation distance of a detection zone for a parallel approach..... | 39 |
| 9.4 | Depth of a detection zone for a parallel approach..... | 39 |
| 10 | Two-hand control devices..... | 40 |
| 10.1 | Two-hand control devices not preventing encroachment..... | 40 |
| 10.2 | Two-hand control devices preventing encroachment..... | 41 |
| 11 | Single control devices..... | 41 |
| 11.1 | Hand-operated single control devices..... | 41 |
| 11.2 | Foot-operated single control devices..... | 42 |
| 12 | Interlocking guards..... | 43 |
| 12.1 | General..... | 43 |
| 12.2 | Interlocking devices without guard locking..... | 43 |
| 12.2.1 | General..... | 43 |
| 12.2.2 | Calculation of the opening e for an interlocking guard with an interlocking device with rotary cam actuated position switch..... | 45 |
| 12.3 | Interlocking devices with guard locking..... | 46 |
| Annex A | (informative) Achieving intended risk reduction..... | 48 |
| Annex B | (informative) Measurement and calculation of system performance to achieve the intended risk reduction..... | 49 |
| Annex C | (normative) Devices with multiple beams or arrangements of single beams with effective detection capability $d_e > 120$ mm or undefined — Number of beams and their height above the reference plane without change in elevation..... | 52 |
| Annex D | (normative) Supplier information for time and distance to achieve the intended risk reduction..... | 54 |
| Annex E | (informative) Variable key for determining separation distance for safeguards..... | 55 |
| Annex F | (normative) Time factors in the overall system response time to achieve the intended risk reduction..... | 64 |
| Annex G | (informative) Explanations of the formulae and values used within this document..... | 67 |
| Bibliography | | 71 |