DIN EN 15051-2:2026-02 (E)

Workplace exposure - Measurement of the dustiness of bulk materials - Part 2: Rotating drum method

Contents

Page

European foreword 3

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Requirements 7
4.1 General 7
4.2 Conditioning of the bulk material 7
4.2.1 As-received condition 7
4.2.2 Conditioning specifications 8
4.3 Sample and environmental control 8
4.4 Moisture content 8
4.5 Bulk density 8
4.6 Test procedure 8
4.7 Replicate tests 8
4.8 In-house test powder 8

5 Rotating drum method 9
5.1 Description of test apparatus 9
5.2 Particle size-selective foams 12
5.3 Sampling filters 12
5.4 Ancillary equipment 13
5.5 Preparation of test sample 13
5.6 Preparation of test apparatus 13
5.7 Running the test apparatus 13
5.8 Weighing the foams and sampling filters 14
5.9 Determination of the inhalable, thoracic and respirable dustiness mass fractions 15
5.10 Limit of detection (LOD) and limit of quantification (LOQ) 16

6 Evaluation of dustiness 17

7 Test report 17

Annex A (normative) Flow rate and leak checks of the rotating drum 19

Annex B (informative) Characteristics of metal foams 20

B.1 General 20
B.2 Structure 20
B.3 Pore size 21
B.4 Chemical composition 21
B.5 Cell diameter 22

Annex C (informative) Test to identify outliers amongst values obtained from repeat tests 23

Annex D (informative) LOD and LOQ procedure for gravimetric sampling filters and foams 25

Bibliography 29