ISO/IEC 80079-38:2026-09 (E)

Explosive atmospheres - Part 38: Equipment and components in explosive atmospheres in underground mines

Contents

Page

FOREWORD 4
INTRODUCTION 9
1 Scope 10
2 Normative references 10
3 Terms, definitions and abbreviated terms 12
4 Requirements for Ex Equipment and Ex Components 13
4.1 General 13
4.2 Ignition hazard assessment 13
4.3 Non-electrical Ex Equipment and Ex Components 14
4.4 Electrical Ex Equipment and Ex Components 14
4.4.1 General 14
4.4.2 Over-current protection 14
4.4.3 Earth-fault protection 15
4.4.4 Charging of cells or batteries 16
4.4.5 Mechanical protection of live parts 16
4.4.6 Electric cables that are part of the Ex Equipment 16
5 Additional requirements for specific Ex Equipment and Ex Components 17
5.1 Cutting and stripping equipment 17
5.1.1 General 17
5.1.2 Mining machines with cutting picks 17
5.1.3 Stripping mining machines 18
5.2 Rope haulages for level and inclined transport 18
5.3 Fans 18
5.3.1 Ventilating fans for use in underground parts of mine 18
5.3.2 Other fans 20
5.4 Internal combustion engines 21
5.5 Air compressors 21
5.6 Ex Equipment and Ex Components for drilling 21
5.7 Brakes 22
5.7.1 Brakes used only for stopping in emergency 22
5.7.2 Service brakes (including friction brakes and fluid based retarders) 22
5.8 Traction batteries, starter batteries and vehicle lighting batteries 22
5.9 Equipment and transmission systems using optical radiation 23
5.10 Electromagnetic and ultrasonic energy radiating equipment 23
5.11 Gas monitoring systems 23
6 EPL Ma equipment having the requisite Level of Protection using a second independent means 23
6.1 General 23
6.2 Requirements for an outer enclosure as the second independent means 23
6.2.1 Temperature rise limits 23
6.2.2 Outer enclosure with free space inside 23

6.2.3 Outer enclosure with no free space inside 24
6.2.4 Prevention of ingress of combustible dust and water 24
6.3 Restriction on internal equipment 24
6.4 Additional type testing for equipment meeting the requisite Level of Protection by a second independent means 24
6.5 Examples of EPL Ma Equipment having two forms of protection listed in 6.3 25
7 Fire protection 26
7.1 General 26
7.2 Non-metallic materials 27
7.3 Hydraulic and pneumatic equipment 27
7.3.1 Hydraulic equipment 27
7.3.2 Pneumatic equipment 27
7.4 Fire resistant fluids 27
7.5 Cable-reeling equipment 28
7.6 Fire prevention on electric cables that are part of the mining machine 29
8 Information for use 29
8.1 Signals and warning notices 29
8.2 Instructions 29
8.2.1 Information on use 29
8.2.2 Information on maintenance and repair 29
9 Marking 30
Annex A (informative) Example of an ignition hazard assessment for a shearer intended for use in an explosive atmosphere of a coal mine 31
A.1 General 31
A.2 EPL and intended use of equipment 31
A.3 Construction/description of the equipment with regard to ignition protection 31
A.4 Ignition control and monitoring system 32
A.5 Compliance with the basic methodology and requirements in IEC 60079-0 and ISO 80079-36 32
A.6 Ignition hazard assessment of the electrical parts of the equipment 33
A.7 Ignition hazard assessment of non-electrical ignition sources 33
A.8 Equipment marking 36
Annex B (informative) Additional guidance 37
B.1 Establishing maximum service temperature 37
B.2 Dust deposits and other material in the gap of moving parts 37
B.3 Short-circuit protection 37
B.4 Earth-fault protection 37
B.5 Electric cables that are part of the equipment 37
B.6 Cutting and stripping equipment 38
B.7 Cable-reeled equipment 38
Bibliography 39

Figure 1 – EPL Ma encapsulation "mb" or powder filling "q" equipment inside a flameproof enclosure "db" or pressurized enclosure "pxb" enclosure with optional intrinsically safe outputs 25
Figure 2 – EPL Ma increased safety "eb" or intrinsically safe "ib" apparatus inside a flameproof "db" or a pressurized "pxb" enclosure 25

Figure 3 – EPL Ma constructional safety "c" inside a flameproof "db" or pressurized "pxb" enclosure 26
Figure 4 – EPL Ma intrinsically safe "ib" or increased safety "eb" apparatus inside an enclosure with encapsulation "mb", or powder filling "q" or "qb" 26
Figure A.1 – Layout and construction of the coal face shearer 32
Table 1 – Combination of materials 20
Table 2 – Limit values for hydraulic fluids 28
Table A.1 – Example of an ignition hazard assessment for a shearer, EPL Mb (1 of 3) 33