

ISO 14119:1998-05 (E)

Safety of machinery - Interlocking devices associated with guards - Principles for design and selection

Contents		Page
1	Scope	1
2	Normative references	1
3	Definitions	2
4	Operating principles and typical forms of interlocking devices associated with guards	3
5	Provisions for the design of interlocking devices (independent of the nature of the energy source)	9
6	Additional technological requirements for electrical interlocking devices	15
7	Selection of an interlocking device	16
Annex A Guard-operated interlocking device with one cam-operated position detector (see Introduction)		18
Annex B Guard-operated interlocking device with tongue-operated switch (see Introduction)		20
Annex C Direct (mechanical) interlocking between guard and start/stop manual control (see Introduction)		22
Annex D Captive-key interlocking device (see Introduction)		24
Annex E Trapped-key interlocking device (see Introduction)		26
Annex F Plug and socket interlocking device (plug/socket combination) (see Introduction)		28
Annex G Guard-operated interlocking device incorporating two cam-operated position detectors (see Introduction)		30
Annex H Mechanical interlocking between a guard and a movable element (see Introduction)		32
Annex J Electrical interlocking device incorporating magnetically actuated (magnetic) switches (see Introduction)		33
Annex K Electrical interlocking device incorporating two proximity detectors (see Introduction)		35
Annex L Pneumatic/hydraulic interlocking devices (see Introduction)		37
Annex M Interlocking device with spring-applied/power-released guard locking device		39
Annex N Interlocking device with guard locking, with manually operated delay device		41
Annex P Bibliography		42