ISO 14119:1998-05 (E)

Safety of machinery - Interlocking devices associated with guards - Principles for design and selection

Contents

Page

1 Scope 1

2 Normative references 1

3 Definitions 2

4 Operating principles and typical forms of interlocking devices associated with guards 3

5 Provisions for the design of interlocking devices (independent of the nature of the energy source) 9

6 Additional technological requirements for electrical interlocking devices 15

7 Selection of an interlocking device 16

Annex A Guard-operated interlocking device with one cam-operated position detector (see Introduction) 18

Annex B Guard-operated interlocking device with tongue-operated switch (see Introduction) 20

Annex C Direct (mechanical) interlocking between guard and start/stop manual control (see Introduction) 22

Annex D Captive-key interlocking device (see Introduction) 24

Annex E Trapped-key interlocking device (see Introduction) 26

Annex F Plug and socket interlocking device (plug/socket combination) (see Introduction) 28

Annex G Guard-operated interlocking device incorporating two cam-operated position detectors (see Introduction) 30

Annex H Mechanical interlocking between a guard and a movable element (see Introduction) 32

Annex J Electrical interlocking device incorporating magnetically actuated (magnetic) switches (see Introduction) 33

Annex K Electrical interlocking device incorporating two proximity detectors (see Introduction) 35

Annex L Pneumatic/hydraulic interlocking devices (see Introduction) 37

Annex M Interlocking device with spring-applied/power-released guard locking device 39

Annex N Interlocking device with guard locking, with manually operated delay device 41

Annex P Bibliography 42