

# DIN EN 14034-2:2006-08 (E)

## Determination of explosion characteristics of dust clouds - Part 2: Determination of the maximum rate of explosion pressure rise $(dp/dt)_{(Index)max}$ of dust clouds

---

| <b>Contents</b>   |  | <b>Page</b> |
|---|--|-------------|
| Foreword .....  |  | 4           |
| Introduction .....  |  | 5           |
| 1 Scope .....   |  | 6           |
| 2 Normative references .....  |  | 6           |
| 3 Terms and definitions .....   |  | 6           |
| 4 Test apparatus .....  |  | 7           |
| 4.1 General .....   |  | 7           |
| 4.2 Explosion vessel .....  |  | 7           |
| 4.3 Dust dispersion system (dust container, fast acting valve, connecting tube, dust disperser) .....                           |  | 8           |
| 4.4 Ignition source .....   |  | 10          |
| 4.5 Control unit .....  |  | 11          |
| 4.6 Pressure measuring system .....   |  | 11          |
| 5 Dust sample .....   |  | 11          |
| 6 Test procedure .....  |  | 11          |
| 7 Calibration and verification .....  |  | 14          |
| 7.1 Calibration .....   |  | 14          |
| 7.2 Verification .....  |  | 14          |
| 8 Safety precautions / instructions .....   |  | 15          |
| 9 Alternative test equipment / procedures .....   |  | 15          |
| 10 Test report .....  |  | 16          |
| Annex A (normative) Electro Pneumatic Valve .....   |  | 17          |
| Annex B (normative) Dust dispenser with 5 mm holes .....  |  | 19          |
| Annex C (normative) 20 l sphere .....   |  | 22          |
| C.1 General .....   |  | 22          |
| C.2 Test apparatus .....  |  | 22          |
| C.3 Test conditions .....   |  | 23          |
| C.4 Test procedure .....  |  | 23          |
| C.5 Calculation of $(dp/dt)_{max}$ , 20 l, $K_{max}$ and $K_{St}$ .....   |  | 24          |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC ..... |  | 25          |
| Bibliography .....  |  | 26          |
| Figures Figure 1 -- 1 m <sup>3</sup> vessel (schematic) .....   |  | 8           |

|  |           |
|--|-----------|
| <b>Figure 2 -- Dust container with blasting cap activated valve as commonly used for explosion suppression (schematic; it is commercially available) .....</b> | <b>9</b>  |
| <b>Figure 3 -- Location of the 6 mm holes in the dust disperser .....</b>  | <b>10</b> |
| <b>Figure 4 -- Dust dispersion and pressure-time curve .....</b>   | <b>13</b> |
| <b>Figure 5 -- Determination of the maximum rate of explosion pressure rise (dp/dt)<sub>max</sub> .....</b>  | <b>14</b> |
| <b>Figure A.1 -- Electro Pneumatic Valve (schematic) .....</b>   | <b>17</b> |
| <b>Figure A.2 -- Discharge characteristic of dust dispersers (without dust) .....</b>  | <b>18</b> |
| <b>Figure B.1 -- Location of the 5 mm holes in the dust disperser .....</b>  | <b>20</b> |
| <b>Figure B.2 -- Rebound nozzle .....</b>  | <b>21</b> |
| <b>Figure B.3 -- Dispersion cup .....</b>  | <b>21</b> |
| <b>Figure C.1 -- Test equipment 20 l sphere (schematic) .....</b>  | <b>23</b> |
| <b>Tables Table 1 -- Maximum permissible deviations SEQ .....</b>  | <b>15</b> |
| <b>Table ZA.1 -- Correspondence between this European Standard and Directive 94/9/EC .....</b>   | <b>25</b> |