

DIN EN 14034-2:2006-08 (E)

Determination of explosion characteristics of dust clouds - Part 2: Determination of the maximum rate of explosion pressure rise $(dp/dt)_{(Index)max}$ of dust clouds

Contents		Page
Foreword		4
Introduction		5
1 Scope		6
2 Normative references		6
3 Terms and definitions		6
4 Test apparatus		7
4.1 General		7
4.2 Explosion vessel		7
4.3 Dust dispersion system (dust container, fast acting valve, connecting tube, dust disperser)		8
4.4 Ignition source		10
4.5 Control unit		11
4.6 Pressure measuring system		11
5 Dust sample		11
6 Test procedure		11
7 Calibration and verification		14
7.1 Calibration		14
7.2 Verification		14
8 Safety precautions / instructions		15
9 Alternative test equipment / procedures		15
10 Test report		16
Annex A (normative) Electro Pneumatic Valve		17
Annex B (normative) Dust dispenser with 5 mm holes		19
Annex C (normative) 20 l sphere		22
C.1 General		22
C.2 Test apparatus		22
C.3 Test conditions		23
C.4 Test procedure		23
C.5 Calculation of $(dp/dt)_{max}$, 20 l, K_{max} and K_{St}		24
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC		25
Bibliography		26
Figures Figure 1 -- 1 m ³ vessel (schematic)		8

Figure 2 -- Dust container with blasting cap activated valve as commonly used for explosion suppression (schematic; it is commercially available)	9
Figure 3 -- Location of the 6 mm holes in the dust disperser	10
Figure 4 -- Dust dispersion and pressure-time curve	13
Figure 5 -- Determination of the maximum rate of explosion pressure rise (dp/dt)_{max}	14
Figure A.1 -- Electro Pneumatic Valve (schematic)	17
Figure A.2 -- Discharge characteristic of dust dispersers (without dust)	18
Figure B.1 -- Location of the 5 mm holes in the dust disperser	20
Figure B.2 -- Rebound nozzle	21
Figure B.3 -- Dispersion cup	21
Figure C.1 -- Test equipment 20 l sphere (schematic)	23
Tables Table 1 -- Maximum permissible deviations SEQ	15
Table ZA.1 -- Correspondence between this European Standard and Directive 94/9/EC	25