

# DIN EN 14994:2007-05 (E)

## Gas explosion venting protective systems

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	6
4	Venting of enclosures .....	7
5	Venting of isolated compact enclosures .....	8
5.1	General .....	8
5.2	Venting of isolated compact enclosures .....	8
5.3	Situations outside the constraints of the basic method (turbulence inducing elements, partially filled enclosures) .....	9
5.3.1	General .....	9
5.3.2	Elevated initial pressure .....	9
5.3.3	Effect of initial turbulence .....	10
5.3.4	Effect of partial filling .....	11
5.3.5	Venting of enclosures containing turbulence inducing elements .....	11
5.4	Elongated enclosures .....	11
5.4.1	General .....	11
5.4.2	Venting of elongated enclosures vented at each end .....	12
5.4.3	Venting of elongated enclosures vented along the enclosure .....	13
5.5	Pipes .....	14
5.6	Interconnected enclosures .....	16
5.7	Vent ducts .....	16
6	Supplementary design aspects .....	17
6.1	General .....	17
6.2	Positioning and shape of explosion vents .....	17
6.3	Choice of venting device .....	17
6.4	External effects .....	18
6.4.1	General .....	18
6.4.2	Flame effects .....	18
6.4.3	Pressure effects .....	18
6.4.4	Deflectors .....	19
6.5	Recoil forces .....	20
7	Information for use .....	21
7.1	Marking .....	21
7.2	Accompanying documents .....	22
Annex A (informative)	Assessment of the level of congestion in rooms containing turbulence including elements .....	23
Annex ZA (informative)	Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC .....	26
Bibliography .....		27
Figures	Figure 1 -- Value of exponent $n$ as a function of $AV/V^{2/3}$ .....	10

<b>Figure 2 -- Pressure reduction of partially filled enclosures as a function of filling ratio .....</b>	<b>11</b>
<b>Figure 3 -- Maximum pressure developed during deflagration of propane-air mixtures flowing at 2 m/s or less in a smooth, straight pipe closed at one end .....</b>	<b>14</b>
<b>Figure 4 -- Vent spacing needed to keep pred from exceeding 0,2 bar for propane in pipes flowing at an initial velocity of between 2 m/s and 20 m/s .....</b>	<b>15</b>
<b>Figure 5 -- Design of a flame deflector plate (basic principles) .....</b>	<b>20</b>
<b>Tables Table A.1 -- Values for the complexity factor c .....</b>	<b>24</b>
<b>Table ZA.1 -- Correspondence between this European Standard and Directive 94/9/EC .....</b>	<b>26</b>