

DIN EN 1177:2008-08 (E)

Impact attenuating playground surfacing - Determination of critical fall height

| Contents | | Page |
|--|---|-------------|
| Foreword | | 3 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Test method | 7 |
| 4.1 | Principle | 7 |
| 4.2 | Apparatus | 7 |
| 4.3 | Accuracy of tests | 8 |
| 4.4 | Conditions for testing | 9 |
| 4.4.1 | Testing in the laboratory | 9 |
| 4.4.2 | Testing on site | 10 |
| 4.5 | Procedure | 10 |
| 4.5.1 | Time/acceleration trace | 10 |
| 4.5.2 | Selection and definition of the test position | 10 |
| 4.5.3 | Procedures for specific types of product | 11 |
| 4.5.4 | Selection of data for determination of critical fall height | 12 |
| 4.6 | Calculation of results | 12 |
| 4.7 | Test report | 13 |
| 4.7.1 | General | 13 |
| 4.7.2 | Tests carried out in the laboratory | 13 |
| 4.7.3 | Tests carried out on site | 13 |
| Annex A (informative) Test rig for determination of critical fall height | | 15 |
| Annex B (informative) Typical examples of trace of acceleration against time and curve of HIC values against drop height | | 16 |