

DIN EN 1177:2018-03 (E)

Impact attenuating playground surfacing - Methods of test for determination of impact attenuation

Contents		Page
European foreword		4
Introduction		6
1	Scope	8
2	Normative references	8
3	Terms and definitions	8
4	Test apparatus	9
4.1	Suitability	9
4.2	Components of the apparatus	10
4.3	Accuracy of apparatus	12
4.3.1	Calibration by a laboratory	12
4.3.2	Checks by operators	12
5	Testing procedure	13
5.1	Principle of impact measurement	13
5.2	Selection and definition of test positions	14
6	Test Method 1 - Determination of Critical Fall Height (CFH)	15
6.1	Principle	15
6.2	Testing in the laboratory	15
6.3	Testing on site	17
7	Test Method 2 - Determination of Impact Attenuation on site	18
7.1	Principle	18
7.2	Selection and recording of test positions	18
7.3	Carrying out the test	19
7.4	Results	19
8	Reports	19
8.1	General	19
8.2	Tests carried out in the laboratory with Method 1	19
8.3	Tests carried out on site in accordance with Method 1	20
8.4	Tests carried out on site in accordance with Method 2	21
Annex A (informative) Test rig for determination of impact attenuation		22
Annex B (informative) Typical examples of trace of acceleration against time and curve of HIC and g _{max} values against drop height		23
Annex C (informative) Verification of computer algorithm used for the calculation of HIC (see 4.3.1.4)		25
Annex D (normative) Procedure for selection of test positions in playgrounds for Method 2 (see Clause 7)		26
D.1	Principle	26
D.2	Criteria for selection of test zones (3.12)	26

Annex E (normative) Method for compaction of loose particulate impact attenuating material (see 6.2.4.5.1)	31
E.1 General	31
E.2 Measurement of layer thickness	31
E.3 Compaction procedure	31
Annex F (informative) Example of a regime for checking the function of an HIC test apparatus	33