

ISO 8364:2017-12 (E)

Alpine skis and bindings - Binding mounting area - Requirements and test methods

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Specifications of free space area	2
4.1	Length of free space area (l_z)	2
4.2	Width of the free space area (b_z)	2
5	Geometrical requirements of free space area	3
5.1	Longitudinal profile of the ski surface within the free space area	3
5.2	Transverse profile of the ski surface within the free space area	3
6	Specifications of binding mounting area	4
6.1	Length of binding mounting area (l_b)	4
6.2	Width of binding mounting area	4
6.3	Minimum thickness of binding mounting area	4
7	Strength requirements of binding mounting area	5
7.1	Screw retention strength (F_r)	5
7.2	Stripping resistance (F_s)	5
8	Specifications of the binding	5
8.1	General	5
8.2	Centre-to-centre distances for binding mounting screws	5
8.2.1	Maximum centre-to-centre distance	5
8.2.2	Minimum centre-to-centre distance	6
8.3	Penetration depth of binding screws	6
9	Side walls	6
10	Marking	6
10.1	Marking of the mounting point	6
10.2	Marking of the ski properties	6
11	Apparatus	6
12	Test screws	8
13	Test methods	8
13.1	Sampling and conditioning	8
13.2	General requirements	8
13.3	Retention strength test	9
13.3.1	Mounting of the attachment plate	9
13.3.2	Positioning of the pull-out tests within the binding mounting area	10
13.3.3	Load application	11
13.4	Stripping resistance test	11
14	Test report	11
Annex A (informative)	Synoptic tables	13