

ISO 4210-2:2023-01 (E)

Cycles - Safety requirements for bicycles - Part 2: Requirements for city and trekking, young adult, mountain and racing bicycles

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vii |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Requirements | 2 |
| 4.1 | Toxicity | 2 |
| 4.2 | Sharp edges | 2 |
| 4.3 | Security and strength of safety-related fasteners | 2 |
| 4.3.1 | Security of screws | 2 |
| 4.3.2 | Minimum failure torque | 2 |
| 4.3.3 | Folding bicycle mechanism | 2 |
| 4.4 | Crack detection methods | 3 |
| 4.5 | Exposed protrusions | 3 |
| 4.6 | Brakes | 3 |
| 4.6.1 | Braking systems | 3 |
| 4.6.2 | Hand-operated brakes | 3 |
| 4.6.3 | Attachment of brake assembly and cable requirements | 4 |
| 4.6.4 | Brake-block and brake-pad assemblies -- Security test | 5 |
| 4.6.5 | Brake adjustment | 5 |
| 4.6.6 | Hand-operated braking-system -- Strength test | 5 |
| 4.6.7 | Back-pedal braking system -- Strength test | 5 |
| 4.6.8 | Braking performance | 5 |
| 4.6.9 | Brakes -- Heat-resistance test | 8 |
| 4.7 | Steering | 8 |
| 4.7.1 | Handlebar -- Dimensions | 8 |
| 4.7.2 | Handlebar grips and plugs | 9 |
| 4.7.3 | Handlebar stem -- Insertion-depth mark or positive stop | 9 |
| 4.7.4 | Handlebar stem to fork steerer -- Clamping requirements | 10 |
| 4.7.5 | Steering stability | 10 |
| 4.7.6 | Steering assembly -- Static strength and security tests | 11 |
| 4.7.7 | Handlebar and stem assembly -- Fatigue test | 12 |
| 4.8 | Frames | 12 |
| 4.8.1 | Suspension-frames -- Special requirements | 12 |
| 4.8.2 | Frame -- Impact test (falling mass) | 13 |
| 4.8.3 | Frame and front fork assembly -- Impact test (falling frame) | 13 |
| 4.8.4 | Frame -- Fatigue test with pedalling forces | 13 |
| 4.8.5 | Frame -- Fatigue test with horizontal forces | 13 |
| 4.8.6 | Frame -- Fatigue test with a vertical force | 13 |
| 4.8.7 | Rear brake mount tests | 14 |
| 4.9 | Front fork | 14 |
| 4.9.1 | General | 14 |
| 4.9.2 | Means of location of the axle and wheel retention | 14 |
| 4.9.3 | Tyre clearance test -- Suspension fork | 14 |
| 4.9.4 | Front fork -- Tensile test | 14 |
| 4.9.5 | Front fork -- Static bending test | 14 |

| | | |
|--------|--|----|
| 4.9.6 | Front fork -- Rearward impact test | 14 |
| 4.9.7 | Front fork -- Bending fatigue test plus rearward impact test | 15 |
| 4.9.8 | Forks intended for use with hub- or disc-brakes | 15 |
| 4.9.9 | Steerer tube -- fatigue test | 15 |
| 4.10 | Wheels and tyre assembly | 16 |
| 4.10.1 | Wheels and tyre assembly -- Rotational accuracy -- Concentricity tolerance and lateral tolerance | 16 |
| 4.10.2 | Wheel and tyre assembly -- Clearance | 16 |
| 4.10.3 | Wheel and tyre assembly -- Static strength test | 16 |
| 4.10.4 | Wheels -- Wheel retention | 16 |
| 4.10.5 | Wheels -- Quick-release devices -- Operating features | 17 |
| 4.10.6 | Wheel and tyre assembly -- Greenhouse effect test for composite wheels | 17 |
| 4.10.7 | Wheel and tyre assembly -- Heat resistance tests for composite rims used in conjunction with rim brake | 18 |
| 4.10.8 | Wheel and tyre assembly -- Overpressure test | 18 |
| 4.10.9 | Wheel and tyre assembly --Information for users | 19 |
| 4.11 | Front mudguard | 19 |
| 4.12 | Pedals and pedal/crank drive system | 19 |
| 4.12.1 | Pedal tread | 19 |
| 4.12.2 | Pedal clearance | 20 |
| 4.12.3 | Pedal -- Static strength test | 21 |
| 4.12.4 | Pedal -- Impact test | 21 |
| 4.12.5 | Pedal -- Dynamic durability test | 21 |
| 4.12.6 | Drive system -- Static strength test | 21 |
| 4.12.7 | Crank assembly -- Fatigue test | 22 |
| 4.13 | Drive-chain and drive belt | 22 |
| 4.13.1 | Drive-chain | 22 |
| 4.13.2 | Drive belt | 22 |
| 4.14 | Chain-wheel and belt-drive protective device | 22 |
| 4.14.1 | Requirements | 22 |
| 4.14.2 | Chain-wheel disc and drive pulley disc diameter | 23 |
| 4.14.3 | Chain and drive belt protective device | 24 |
| 4.14.4 | Combined front gear-change guide | 25 |
| 4.15 | Saddles and seat-posts | 25 |
| 4.15.1 | Limiting dimensions | 25 |
| 4.15.2 | Seat-post -- Insertion-depth mark or positive stop | 25 |
| 4.15.3 | Saddle/seat-post -- Security test | 26 |
| 4.15.4 | Saddle and saddle rail -- Static strength test | 26 |
| 4.15.5 | Saddle and seat-post assembly -- Fatigue test | 26 |
| 4.15.6 | Seat-post -- Fatigue test | 26 |
| 4.16 | Spoke protector | 27 |
| 4.17 | Luggage carriers | 27 |
| 4.18 | Road test of a fully assembled bicycle | 27 |
| 4.19 | Lighting systems and reflectors | 27 |
| 4.19.1 | General | 27 |
| 4.19.2 | Wiring harness | 27 |
| 4.19.3 | Lighting systems | 28 |
| 4.19.4 | Reflectors | 28 |
| 4.20 | Warning device | 28 |
| 5 | Manufacturer's instructions | 28 |
| 6 | Marking | 30 |
| 6.1 | Requirement | 30 |
| 6.2 | Durability test | 31 |
| | Annex A (informative) Steering geometry | 32 |
| | Bibliography | 33 |