

DIN EN 1177:2024-10 (E)

Impact attenuating playground surfacing - Methods of test for determination of impact attenuation (includes Amendment :2023)

| Contents | | Page |
|-----------------------------|---|-------------|
| European foreword | | 4 |
| Introduction | | 6 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms and definitions | 8 |
| 4 | Test apparatus | 9 |
| 4.1 | Suitability | 9 |
| 4.2 | Components of the apparatus | 10 |
| 4.2.1 | General | 10 |
| 4.2.2 | Headform | 10 |
| 4.2.3 | Signal conditioner (optional) | 10 |
| 4.2.4 | Guidance system | 10 |
| 4.2.5 | Fall height measuring equipment | 11 |
| 4.2.6 | Release system | 11 |
| 4.2.7 | Signal transmission system | 11 |
| 4.2.8 | Impact measuring equipment | 11 |
| 4.3 | Accuracy of apparatus | 12 |
| 4.3.1 | Calibration by a laboratory | 12 |
| 4.3.2 | Checks by operators | 12 |
| 5 | Testing procedure | 13 |
| 5.1 | Principle of impact measurement | 13 |
| 5.1.1 | General | 13 |
| 5.1.2 | Time/acceleration curve | 13 |
| 5.1.3 | Calculation of results | 14 |
| 5.2 | Selection and definition of test positions | 14 |
| 5.3 | !Testing onsite conditions | 15 |
| 6 | Test Method 1 - Determination of Critical Fall Height (CFH) | 15 |
| 6.1 | Principle | 15 |
| Table 1 -- HIC values | | 15 |
| 6.2 | Testing in the laboratory | 16 |
| 6.3 | Testing on site | 18 |
| 7 | Test Method 2 - Determination of Impact Attenuation on site | 19 |
| 7.1 | Principle | 19 |
| 7.2 | Selection and recording of test positions | 19 |
| 7.3 | Carrying out the test | 19 |
| 7.4 | Results | 20 |
| 8 | Reports | 20 |
| 8.1 | General | 20 |
| 8.2 | Tests carried out in the laboratory with Method 1 | 20 |
| 8.3 | Tests carried out on site in accordance with Method 1 | 21 |
| 8.4 | Tests carried out on site in accordance with Method 2 | 22 |

| | |
|--|-----------|
| Annex A (informative) Test rig for determination of impact attenuation | 23 |
| Figure A.1 -- Test rig for determination of critical fall height | 23 |
| Annex B (informative) Typical examples of trace of acceleration against time and curve of HIC and gmax values against drop height | 24 |
| Figure B.1 -- Typical trace of acceleration against time | 24 |
| Figure B.2 -- Example of typical curves from a test on rubber tiles for HIC and gmax values against drop height | 25 |
| Annex C (informative) Verification of computer algorithm used for the calculation of HIC (see 4.3.1.4) | 26 |
| Table C.1 -- Calculation of the output voltage for a 20 kHz frequency | 26 |
| Annex D (normative) Procedure for selection of test positions in playgrounds for Method 2 (see Clause 7) | 27 |
| D.1 Principle | 27 |
| D.2 Criteria for selection of test zones (3.12) | 27 |
| Table D.1 -- Example for test zones - Swings | 28 |
| Table D.2 -- Example for test zones - Slides and cableways | 29 |
| Table D.3 -- Example for test zones - Carousels | 30 |
| Table D.4 -- Example for test zones - Rocking equipment and spatial nets | 30 |
| Annex E (normative) Method for compaction of loose particulate impact attenuating material (see 6.2.4.5.1) | 32 |
| E.1 General | 32 |
| E.2 Measurement of layer thickness | 32 |
| E.3 Compaction procedure | 32 |
| Table E.1 -- Dimension of board sizes that can be used by different weight testers | 33 |
| Annex F (informative) Example of a regime for checking the function of an HIC test apparatus | 34 |
| Table F.1 -- Example of a regime for checking the correct function of an HIC test apparatus used weekly | 34 |
| Annex G (Informative) !History of HIC testing of impact attenuating surfaces for playgrounds and variations in test results | 35 |