

DIN EN ISO 6185-3:2024-10 (E)

Inflatable boats - Part 3: Boats with a length of the hull less than 8 m with a motor power rating of 15 kW and greater (ISO 6185-3:2024)

Contents		Page
European foreword		4
Annex ZA (informative) Relationship between this European Standard and the essential requirements of Directive 2013/53/EU		5
Foreword		11
Introduction		12
1 Scope		13
2 Normative references		13
3 Terms and definitions		15
4 Symbols and abbreviated terms		16
5 Construction and structural requirements		17
5.1 Structural materials.....		17
5.1.1 General.....		17
5.1.2 Materials forming the flexible floor and buoyancy tube.....		17
5.1.3 Wood.....		18
5.2 Buoyant material used in foam-filled buoyancy tubes.....		19
5.2.1 General.....		19
5.2.2 Tests.....		19
5.3 Lifting the boat.....		20
5.3.1 General.....		20
5.3.2 Fittings for lifting of the boat (if applicable).....		20
5.3.3 Complete boat overload test.....		20
5.4 Strength of the boat's structure.....		20
5.4.1 General.....		20
5.4.2 Drop test (rigid inflatable boats only).....		21
5.4.3 In-water testing.....		21
5.5 Buoyancy tube attachment strength test (type test only).....		23
5.5.1 General.....		23
5.5.2 Requirement.....		23
5.6 Strength of principal fitted accessories.....		23
5.6.1 General.....		23
5.6.2 Requirement.....		23
6 Stability and flotation requirements		23
6.1 General.....		23
6.2 Maximum load capacity.....		24
6.2.1 Determination methods.....		24
6.2.2 Crew limit.....		24
6.3 Offset load test.....		25
6.4 Buoyancy requirements.....		25
6.4.1 Total buoyant volume.....		25
6.4.2 Buoyancy determination.....		26
6.4.3 Sub-division of the inflatable buoyancy tubes (chambers).....		26
6.4.4 Nominal pressures (inflatable buoyancy tubes).....		27
6.4.5 Valves (if applicable).....		27
6.4.6 Strength of the inflatable buoyancy tube.....		28
6.5 Level flotation when swamped.....		29
6.6 Watertightness.....		29
6.6.1 Openings and flooding.....		29

6.6.2	Hull (below deck) drainage.....	29
6.6.3	Watertightness test (not applicable to self-draining boats).....	30
6.7	Cockpit draining time assessment (Type VIII boats only).....	30
6.7.1	Requirements.....	30
6.7.2	Self-draining test requirement.....	30
6.7.3	Test method.....	30
6.7.4	Quick-draining calculation requirement.....	30
7	Requirements for safe operation	30
7.1	Determination of maximum motor power and manoeuvring speed.....	30
7.2	Prevention of falling overboard and recovery.....	30
7.2.1	General.....	30
7.2.2	Location of handholds fitted on tubes of high-speed boats.....	31
7.2.3	Seating safety sign.....	31
7.3	Seating and attachment systems (where offered as a standard or optional equipment).....	31
7.4	Field of vision from the helm position.....	32
7.5	Fire protection.....	32
7.6	Rowlocks and oars.....	32
7.6.1	Requirements.....	32
7.6.2	Abrasion damage.....	32
7.6.3	Prevention from loosening.....	32
7.6.4	Strength of rowlocks.....	32
7.6.5	Use of the rowlocks and oars.....	32
7.6.6	Rowing test.....	32
8	Installation requirements	33
8.1	Motor and motor spaces.....	33
8.1.1	Inboard motors.....	33
8.1.2	Outboard motors.....	33
8.2	Ventilation of petrol engine and/or petrol tank compartments (where applicable).....	33
8.3	Electrical installations (where offered as standard or optional equipment).....	33
8.4	Fuel systems.....	33
8.5	Remote steering system (where offered as standard or optional equipment).....	33
8.6	Gas systems.....	34
8.7	Navigation lights.....	34
8.8	Discharge prevention.....	34
9	Equipment to be supplied with the boat	34
10	Builder's plate(s) and craft identification number	34
11	Owner's manual	34
Annex A (normative)	Buoyancy tube attachment tests	35
Annex B (normative)	Strength of principal fitted accessories	37
Bibliography	39

