

DIN EN 17860-5:2025-06 (E)

Carrier cycles - Part 5: Electrical aspects

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | General requirements | 7 |
| 4.1 | Risk assessment | 7 |
| 4.2 | Significant hazards and safety functions | 7 |
| 4.2.1 | Significant hazards | 7 |
| 4.2.2 | Safety function for control system of carrier EPAC | 8 |
| 4.3 | Prevention of unauthorized use | 8 |
| 5 | Electrical requirements | 8 |
| 5.1 | Electric system | 8 |
| 5.2 | Controls and symbols | 8 |
| 5.3 | Battery | 9 |
| 5.4 | External battery charger | 9 |
| 5.5 | Electric cables and couplers | 9 |
| 5.5.1 | General | 9 |
| 5.5.2 | Requirements | 9 |
| 5.5.3 | Test method | 9 |
| 5.6 | Wiring | 9 |
| 5.7 | Power cables and conduits | 10 |
| 5.8 | External and internal electrical connections | 10 |
| 5.9 | Moisture resistance | 10 |
| 5.10 | Mechanical strength test of the electrical components | 10 |
| 5.10.1 | General | 10 |
| 5.10.2 | Function related shock test | 11 |
| 5.10.3 | Impact related shock test - Lateral overturning | 11 |
| 5.11 | Maximum speed for which the electric motor gives assistance | 11 |
| 5.11.1 | Requirements | 11 |
| 5.11.2 | Test method | 11 |
| 5.12 | Walk and manoeuvring assistance mode | 12 |
| 5.12.1 | Requirements | 12 |
| 5.12.2 | Test method | 12 |
| 5.13 | Power management | 13 |
| 5.13.1 | Requirements | 13 |
| 5.13.2 | Test method - Auxiliary electric motor management | 14 |
| 5.14 | Measurement of the maximum continuous rated power | 15 |
| 5.14.1 | Requirements | 15 |
| 5.14.2 | Measurement | 15 |
| 5.14.3 | Alternative measurement | 15 |
| 5.15 | Electromagnetic compatibility | 16 |
| 5.15.1 | Emission | 16 |
| 5.15.2 | Immunity | 16 |
| 5.15.3 | Carrier EPAC in mains charging mode | 16 |
| 5.16 | Failure mode | 17 |

| | | |
|--|---|----|
| 5.16.1 | Acoustical and / or visual warning | 17 |
| 5.17 | Anti-tampering measures | 17 |
| 5.18 | Thermal hazards | 17 |
| 5.18.1 | Non-continuous contact surface | 17 |
| 5.18.2 | Continuous contact surface | 17 |
| 5.18.3 | Ambient temperature | 17 |
| 5.19 | Recuperative braking | 18 |
| 5.19.1 | Braking | 18 |
| 5.19.2 | Brake light activation by recuperative braking | 18 |
| 5.20 | Electrical requirements for electric cargo trailers | 18 |
| 5.20.1 | Control for electric cargo trailers | 18 |
| 5.20.2 | Handcart mode for electric cargo trailers - Handcart mode speed test | 18 |
| 5.20.3 | Maximum speed test | 18 |
| 5.20.4 | Assistance power for electric cargo trailer | 18 |
| 5.20.5 | Activating the trailer mode | 23 |
| 5.20.6 | Plug connections for electric cargo trailers | 23 |
| 5.20.7 | Performance levels (PLrs) for control system of electric cargo trailers | 24 |
| Annex A (normative) Electromagnetic compatibility of carrier EPAC and ESA | | 26 |
| Annex B (normative) Light, warning device, on/off symbols | | 27 |
| Annex C (informative) Walk and manoeuvring assistance mode symbols | | 28 |
| Annex D (informative) Measurement of the maximum continuous rated power -- Alternative measurement | | 29 |
| Bibliography | | 31 |